


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

CENTER QUARTER Corner of Section 11, Township 144, Range 30, 5th P.M.
STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

- On 3/5/81 found a GLO brass cap monument as set in 1930.
DATE
- left monument as found, lowered monument, removed monument (explain)
- On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES



BEARINGS ARE APPROXIMATE

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Doug H. Stevens 9-11-82
SIGNATURE DATE

Registration No. 12604

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

264951
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 10:04 A.M. on the 14 day of Sept. A.D., 19 82

County Recorder Dorothy Hendrick

By MS, Deputy

DOCUMENT NO. 264951

Statement of Evidence:

- 1930 U.S. General Land Office dependent resurvey established this corner and an iron pipe with a marked brass cap was set to mark the corner. The following bearing trees were marked: 7" Birch S 57 E 187 links and 12" N. Pine N 89 W 206 links.
- 1981 U.S. Forest Service technician G. Brama found the corner monumented with a GLO brass cap monument in good condition up 5". The following bearing trees were found: 12" Birch S 57 E 187 links and N. Pine stub N 89 W 206 links. Three new bearing trees were marked and are shown on this certificate. Steel sign posts were set 3.0' east and 2.95' west of the corner.
- 1982 Analysis of the above data indicates that the location of this Government corner has been perpetuated. I accepted the monument as marking the corner location as when set in 1930 by the GLO resurvey based on bearing tree evidence.