

C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the Southeast Corner of Section 16, Township 141 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On July 1, 1985, to mark this corner position, we set a 2.5 inch (outside diameter) by 24 inch long galvanized iron pipe with a 3 inch diameter brass tablet, 10 inches below the road surface, and stamped as shown.

SKETCH OF REFERENCE TIES

(not to scale)

Top of page is NORTH


decl: 5° E

N 42° W, 37.50 feet to a 2.5 foot by 2.5 foot Boulder, scribed "S16" facing the monument.



F.R. 2106

N 41° E, 40.03 feet to a 16d nail in the southeasterly face of a 6.7 inch diameter White Birch, double blazed and scribed "S15" and "BT".



F.R. 2106A

S 43° W, 79.20 feet to a 16d nail in the northwesterly face of a 5.3 inch diameter Maple, double blazed and scribed "S21" and "BT".



S 45° E, 33.42 feet to a 16d nail in the northeasterly face of a 5.6 inch diameter White Birch, double blaze and scribed "S22" and "BT".



All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date 9-24-85 Registration No. 14677

285572
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 19 85, at 9:45 A.M. and assigned DOCUMENT NUMBER 285572.

Claudia Kozler
County Recorder
mj

STATEMENT OF EVIDENCE: Southeast Corner of Section 16, Township 141 North, Range 25 West, of the 5th Principal Meridian.

This corner was originally established by Edgar P. Putman and William P. Allen, Deputy Surveyors, in April of 1871. The record of that survey is on file in the Office of the Secretary of State, St. Paul, Minnesota. Their notes indicate that a post was set to mark the corner and referenced by: a 26 inch diameter Aspen that bears NORTH 52 degrees WEST, a distance of 15 links (9.90 feet); a 10 inch diameter Fir that bears SOUTH 60 degrees WEST, a distance of 29 links (19.14 feet); a 6 inch diameter Fir that bears SOUTH 13 degrees EAST, a distance of 26 links (17.16 feet); and a 12 inch diameter Spruce that bears NORTH 70 degrees EAST, a distance of 14 links (9.24 feet).

In 1913, J. H. Flynn, Cass County Surveyor, recovered the original government survey Aspen and the northeasterly Fir. He then set a post from these trees and made the following new references: a 20 inch diameter White Pine stump that bears NORTH 61 degrees EAST, a distance of 42.0 feet; and a 36 inch diameter Large Boulder that bears NORTH 49 degrees 30 minutes WEST, a distance of 37.5 feet. This information was found in the Cass County SURVEYOR'S RECORD, Book "C", page 37.

In 1917, J. H. Flynn returned to this corner and traversed south from here. He lists all the same references as in 1913. This information can be found in the Cass County SURVEYOR'S RECORD, Book "C", page 32.

On June 13, 1985, a Forest Service survey crew recovered both the White Pine stump and the large Boulder from the 1913 Cass county survey. They pulled record bearings and distances from the recovered evidence and established a point which fell in the centerlines intersection of roads running north, south, and east. I used the recovered 1913 survey evidence to perpetuate the original government survey and accept it as the corner.

A Forest Service survey crew returned to this area on July 1, 1985, and set a new monument and references as shown on the sketch. This information is on file with the USDA Forest Service, Chippewa National Forest.