

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the North Quarter Corner of Section 23, Township 141 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On August 5, 1985, to mark this corner position, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES

decl: 5° E

(not to scale)

Top of page is NORTH

N 8° W, 35.54 feet to a 16d nail in the easterly face of a 7.1 inch diameter Sugar Maple, double blazed and scribed "1/4 S14" and "BT".



8 foot long metal post with 54-2 "Property Boundary" and 54-9 "Land Survey Monument" signs attached.



8 foot long metal post with a 54-2 "Property Boundary" sign attached.

S 75° E, 60.85 feet to a 16d nail in the northerly face of an 8.2 inch diameter White Birch, double blazed, scribed "1/4 S23" and "BT".

SOUTH, 13.20 feet to the North-west corner of the 1917 Large Boulder 7 feet by 5.5 feet by 2.5 feet high.

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*  
Kenneth L. Whitehorn

Date 9-25-85 Registration No. 14677

285573  
OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 19 85, at 9:50 A.M. and assigned DOCUMENT NUMBER 285573.

*Clondine Kayser*  
County Recorder  
M.S.

**STATEMENT OF EVIDENCE:** North Quarter Corner of Section 23, Township 141 North, Range 25 West, of the 5th Principal Meridian.

This corner was originally established by Edgar P. Putman and William P. Allen, Deputy Surveyor's, in April of 1871. The record of that survey is on file in the Office of the Secretary of State, St. Paul, Minnesota. Their notes indicate that a post was set to mark the corner and referenced by: an 8 inch diameter Cedar that bears NORTH 15 degrees EAST; a distance of 13 links (8.58 feet); and a 7 inch diameter Fir that bears SOUTH 46 degrees WEST, a distance of 12 links (7.92 feet).

In 1917, J. H. Flynn, Cass County Surveyor, recovered an old post from which: a 10 inch diameter Cedar that bears NORTH 15 degrees EAST, a distance of 13 links (8.58 feet); and a 7 inch diameter Fir that bears SOUTH 46 degrees WEST, a distance of 12 links (7.92 feet). He then established a Large Boulder that bears SOUTH, a distance of 13.2 feet to it's west end. This information was found in the Cass County SURVEYOR'S RECORD, Book "C", page 35.

On August 5, 1985, a Forest Service survey crew found a Large Boulder but no traces of any other survey evidence. This is the only boulder in the area and I feel it is probably the 1917 Flynn boulder. We set a new monument and references as shown on the sketch using the 1917 bearing and distance from the boulder. This information is on file with the USDA-Forest Service, Chippewa National Forest.