

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the West One-sixteenth Corner on the South Line of Section 4, Township 144 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On May 2, 1985, at said corner position, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe with a 3 inch diameter brass tablet up 18 inches and stamped as shown in the sketch.


SKETCH OF REFERENCE TIES
(not to scale)

compass decl: 5° E



N 38° W, 26.21 feet to a 16d nail in a 6.5 inch diameter Ash, double blazed and scribed "W1/6 S4" and "BT".

N 62° E, 17.63 feet to a 16d nail in a 10.2 inch diameter White Oak, double blazed and scribed "W1/16 S4" and "BT".



8 foot long metal post with a 54-2 "PROPERTY BOUNDARY sign attached.

8 foot long metal post with a 54-2 "PROPERTY BOUNDARY and a 54-9 "LAND SURVEY MONUMENT" signs attached.

S 37° W, 65.30 feet to a 16d nail in an 8.6 inch diameter Cedar, double blazed and scribed "W1/16 S9" and "BT".



All bearing trees are marked with red enamel, a USFS 54-3 'BEARING TREE TAG', and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date 9-24-85 Registration No. 14677

285575
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov, 1985, at 10:40 A.M. and assigned DOCUMENT NUMBER 285575.

Claudine Kayler
County Recorder
MS

STATEMENT OF EVIDENCE: The West One-sixteenth Corner on the South Line of Section 4, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original survey of this township by Benjamin C. Baldwin, Deputy Surveyor, in 1876.

No record was found of establishment or visitation through the intervening years for this corner position. A thorough search of the area failed to turn up any evidence of this corner position. Based on this information we established this corner position midpoint and on line between the South Quarter Corner and the Southwest Corner of said Section 4. For a complete history of the South Quarter Corner see James Parker, R.L.S., "CERTIFICATE OF LOCATION OF GOVERNMENT CORNER", on file in the Office of the Cass County Recorder as Document Number 281671 and for the Southwest Corner see James Parker, R.L.S., "CERTIFICATE OF LOCATION OF GOVERNMENT CORNER", on file in the Office of the Cass County Recorder as Document Number 281670. The basis for the determination of the subdivisional lines for this section are: Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700; coordinates on the corners of the Public Land Survey System. These coordinates were provided to the USDA-Forest Service (USFS) by Advance Surveying and Engineering Company, Minneapolis, Minnesota, under contract to perpetuate and restore the Public Land Survey System corners in this township.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary.