


C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the South One-Sixteenth Corner on the East Line of Section 21, Township 144 North, Range 25 West of the   th Principal Meridian, STATE OF MINNESOTA, County of Cass.


On May 20, 1985, to mark this corner position, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES  
(not to scale)

decl: 5° E



N 63° W, 77.21 feet to a 16d nail in the northeasterly face of a 13.2 inch diameter Cedar, double blazed and scribed "S1/16 S21" and "BT".



8 foot long metal post with USFS 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.

3.0 ft

3.0 ft

8 foot long metal post with a USFS 54-2 "PROPERTY BOUNDARY" sign attached.



S 5° E, 27.35 feet to a 16d nail in the westerly face of an 8.7 inch diameter Spruce, double blazed and scribed "S1/16 S22" and "BT".

S 64° W, 51.02 feet to a 16d nail in the southeasterly face of a 12.7 inch diameter Cedar, double blazed and scribed "S1/16 S21" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*  
Kenneth L. Whitehorn

Date Sep 26, 1985 Registration No. 14677

285584  
OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov., 1985, at 10:50 A.M. and assigned DOCUMENT NUMBER 285584.

*Claudine Keyler*  
County Recorder  
M.S.

**STATEMENT OF EVIDENCE:** The South One-sixteenth Corner on the East Line of Section 21, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original survey of this township by Benjamin C. Baldwin, Deputy Surveyor, in 1876.

No public record was found of establishment or visitations through the intervening years for this corner position. A thorough search was made of the area but no evidence of this corner position was recovered. Based on this information we established this corner position midpoint on the East Line of the Southeast Quarter of said Section 21. The basis for the determination of this point are coordinates on the corners of the Public Land Survey System provided to the USDA-Forest Service (USFS) by Advance Surveying and Engineering Company, Minneapolis, Minnesota, under contract to perpetuate and restore the Public Land Survey System corners in this township. These coordinates are Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary. Records of this survey are on file with the USDA-Forest Service, Chippewa National Forest.