

**CERTIFICATE OF LOCATION OF GOVERNMENT CORNER**

For the West One-sixteenth Corner on the North Line of Section 11, Township 141 North, Range 30 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On April 20, 1983, to mark this corner position, we set a 2.5 inch (outside diameter) by 24 inch long galvanized iron pipe topped with a 3 inch diameter brass tablet, 1.5 inches below the road surface and stamped as shown in the sketch.

**SKETCH OF REFERENCE TIES**

Top of Page is NORTH

(not to scale)

decl: 5° E

N 60° W, 128.43 feet to a nail on the side of a 14 inch diameter Jack Pine, single blazed and scribed "W1/16 S2 BT".

N 4° W, 151.95 feet to a nail on the side of a 20 inch diameter Norway Pine, single blazed and scribed "W1/16 S2 BT".

Center Line of MN Trunk Highway 200



2.0 feet

S 52° E, 85.64 feet to an "X" chiseled on top of a 6 foot by 9 foot by 30 inches high rock.

S 58° W, 154.40 feet to a nail on the side of a 21 inch diameter Norway Pine, not scribed or painted.

All bearing trees are marked with red enamel, and a USFS 54-3 "BEARING TREE TAG" unless otherwise noted.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*  
Kenneth L. Whitehorn

Date FEB. 25 1986 Registration No. 14677

287746  
OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 14 day of March, 19 86, at 1140 P.M. and assigned DOCUMENT NUMBER 287746.

*Claudine Kaylor*  
Claudine Kaylor, County Recorder  
m j

**STATEMENT OF EVIDENCE:** West One-sixteenth Corner on the North Line of Section 11, Township 141 North, Range 30 West of the 5th Principal Meridian.

In 1917, Earl G. Harrington, U.S. Surveyor of the General Land Office, executed a dependent resurvey and subdivision of sections in this township under instruction in Group 2, Minnesota, issued September 11, 1917. He established this corner position using proportionate methods and set a 1 inch diameter by 36 inch long iron post monument with a brass cap, marked to identify the corner, witnessed by the following bearing trees: A 10 inch diameter Jack Pine which bears NORTH 75 1/2 degrees WEST a distance of 48 links (31.68 Feet) and a 14 inch diameter Jack Pine which bears SOUTH 70 degrees EAST a distance of 29 links (19.14 feet).

This corner position lies in Minnesota Trunk Highway Number 200 but the plans and notes on file with the Brainerd Office of the Minnesota Department of Transportation contain no record of the recovery of this corner position.

Between February 23 and April 18, 1983 a traverse was run by the U.S. Forest Service on the North line of Section 11. No evidence of the GLO iron or witnesses was recovered and this position was determined lost.

On April 20, M. Hayes, C. Krause, G. Brama, and J. Allison, U.S. Forest Service; and T. Freeman, Cass County Surveyor's Office, established the monument and witnesses as shown on the front of this form. This corner position was re-established on line and at proportionate distance between the re-established North Quarter Corner of Section 11 (by U.S. Forest Service this same date) and the re-established Northwest Corner of Section 11 (Certificate of Location of Government Corner by Walter E. Curo, dated December 8, 1981 on file and of record in the Office of County Recorder, Cass County, Walker, Minnesota and filed as document number 262618.).