

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the Southeast Corner of Section 12, Township 143 North, Range 27 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On May 20, 1986, to mark this corner position, we set a 5/8 inch (outside diameter) by 60 inch long Aluminum rod and topped with a 3-1/4 inch diameter Aluminum tablet, up 1.1 ft. and stamped as shown in the sketch.


SKETCH OF REFERENCE TIES

Top of Page is NORTH

(not to scale)

decl: 5° E

N-78° W, 85.47 to a 16d nail in the North face of a 14.1 inch Tamarack, double blazed and scribed "S12" and "BT".



3:0 ft ←

8 ft. Carsonite Boundary post with 54-2a "PROPERTY BOUNDARY" and LSM 130 "LAND SURVEY MONUMENT" signs.

S-21° W, 68.33 feet to a 16d nail in the East face of a 14.3 inch diameter Cedar, double blazed and scribed "S13" and "BT".

S-67° E, 26.40 feet to a 16d nail in the north face of a 7.4 inch Cedar, double blazed and scribed "S18" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn

Kenneth L. Whitehorn

Date JUN. 19 1986 Registration No. 14677

289683
OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 29 day of

June, 19 86, at 10:20 A.M. and assigned DOCUMENT

NUMBER 289683

Claudine Kaylor

Claudine Kaylor, County Recorder

STATEMENT OF EVIDENCE: For the Southeast Corner of Section 12, Township 143 North, Range 27 West of the 5th Principal Meridian.

This corner position was originally established by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office (GLO) now the Bureau of Land Management (BLM). On August 23, 1872, Mr. Griffin set a post of unspecified type, to mark this corner position which was witnessed by: a 6 inch diameter Cedar that bears SOUTH 32 degrees EAST, a distance of 10 links (6.60 feet); an 8 inch diameter Spruce that bears NORTH 51 degrees EAST, a distance of 21 links (13.86 feet); an 8 inch diameter Spruce that bears SOUTH 37 degrees 30 minutes WEST, a distance of 20 links (13.20 feet); and a 6 inch diameter Spruce that bears NORTH 50 degrees WEST, a distance of 24 links (15.84 feet).

No intervening record of any visitation or survey work utilizing this corner position was recovered. A thorough search was conducted but we were unable to recover any physical evidence to indicate this corner position. I determined the lost position for this corner using single proportionate methods (between the Southeast Corner of Section 13 and the Northeast Township Corner) and set the monument and references as shown on the front of this document. This lost position fits within one-half chain (33 feet) of the original call to Bear Creek to the north of the corner.