

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 1, Township 141 N., Range 28 W., 5th P.M.
 STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

On 7/14/87 found a 1"x36" GLO brass cap monument, bent over
DATE

left monument as found, lowered monument, removed monument (explain)

On 7/14/87 placed a 2"x50 1/4" galv. I.P. with stamped brass cap
DATE

SKETCH OF REFERENCE TIES



Not to scale



Trees double blazed, scribed, painted red and 54-3 Bearing Tree tag attached.
 Measurement taken to nail in side of tree.

Statement of evidence relative to this corner location is on back of page. 301667

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Walt G. Coon 11-23-87
SIGNATURE DATE

Registration No. 11395

- Land Surveyor
- County Surveyor

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 9:10 A .M. on the 16 day of December A.D., 19 87

County Recorder Claudine Kayser

By ms, Deputy

DOCUMENT NO. 301667

Statement of Evidence: North Quarter Corner Section 1, T.141 N., R. 28 W., 5th P.M.

- 1873 US General Land Office survey set a wood post for this corner and marked the following bearing trees: 9" Ironwood S 40°E 15 lks., 5" Ironwood N 55°W 25 lks.
- 1918 US General Land Office dependent resurvey set a 1"x36" I.P. with marked brass cap at proportional position. The following bearing trees were marked: 8" Maple S 5°E 36 lks., 20" Red Oak N 55°W 28 lks.
- 1972 US Forest Service personnel looked for corner. Notes show corner falls near edge of plantation-no evidence found.
- 1987 Walt Curo, under contract with the US Forest Service, found the GLO brass cap monument bent over. Replaced with 2"x 50½" galv. I.P. with marked brass cap.