

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTH QUARTER Corner of Section 36, Township 141N, Range 29W, 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch: Latitude: 46° 59' 40.523"
 Longitude: 94° 17' 36.832"


On 5-25-88 found a 2" iron monument with brass cap (USFS)
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

Magnetic Decl: 5° East SKETCH OF REFERENCE TIES
 Not to Scale

All distances are horizontal to nail in side of tree.



 8" Norway Pine
 N 17 W 25.32'
 (1983 BT)

 5" Norway Pine
 S 85 E 19.64'

15" Jack Pine
 S 48 E 37.45'
 (1983 BT)

Monument Stamped

Monument is located approx.
 150' north of woods trail
 northeast-southwest
 8' sign post south 5.0'
 8' sign post west 5.0'


T 141 N
 R 29 W
 S 25
 1/4 _____
 S 36
 1982

All trees are painted with red enamel and marked with a 54-3 (bearing tree) tag.

R.L.S. No. 13298

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.


 David S. Landecker

Date 3/31/89 Registration No. 17008

311175

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 12:25 P.M. on the 3rd day of April A.D., 1989

County Recorder (Claudine Kaylor)

By DJK, Deputy

DOCUMENT NO. 311175

Statement of Evidence:

North Quarter Corner Section 36, Township 141
North, Range 29 West, Cass County, Minnesota

V-23 141-29
Bk.4 Pg.24

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 29 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 20 inch White Pine North 40 degrees East a distance of 13 links; and a 24 inch White Pine North 55 degrees West a distance of 39 links.

U.S. Forest Service records show the following: old field book shows form 458 on a Jack Pine North 64 degrees East a distance of 42.24 feet.

1964 U.S. Forest Service records show the following: technician Ekstrom found an old C.C. tag.

1983 Dave Claypool, Licensed Land Surveyor Number 13298, under USFS contract, found metal tag on Jack Pine. No original evidence was found. Corner was established at lost position. He set a 2 inch by 60 inch iron pipe with brass cap and marked the following bearing trees: a 5 inch Norway Pine North 17 degrees West a distance of 25.30 feet; a 14 inch Jack Pine South 48 degrees East a distance of 37.43 feet; and a 10 inch Red Oak South 35 degrees West a distance of 13.65 feet. Filed Corner Certificate with the Cass County Recorder as document Number 279155.

1986 U.S. Forest Service crews set an aerial target over this corner position for determination of coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner. The 1983 Oak bearing tree was cut off.

1988 on May 25 a Landecker-Stevenson & Associates crew visited the corner and found the following evidence: 2 inch brass cap monument in good condition, and 1983 bearing trees Northwest and Southeast as shown on front of this certificate. One new bearing tree was marked as shown and steel sign posts set as noted on front of this certificate.