

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter \_\_\_\_\_ Corner of Section 29, Township 141 N, Range 28 W, 5th P.M.

STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

Latitude: 47° 00' 02.776"  
Longitude: 94° 14' 51.136"

On 11/4/88 found a 1" GLO iron pipe with brass cap.  
DATE


left monument as found,  lowered monument,  removed monument (explain)

On \_\_\_\_\_ placed a \_\_\_\_\_  
DATE

Magnetic Decl: 5° East  
Not to Scale

### SKETCH OF REFERENCE TIES

All distances are horizontal to nail in side of tree.



  
20" Norway Pine  
N 7 W 191.40'  
(1918 GLO)

  
9" Burr Oak  
S 58 E 81.70'

  
13" Burr Oak  
S 36 E 86.40'

Monument is located in Northerly portion of swamp 70'± Southerly of East-West trail.  
8' steel sign post East 5.0'  
8' steel sign post South 4.0'

Monument Stamped


All trees are painted with red enamel and marked with a 54-3 (bearing tree) tag.

<sup>1/2</sup>  
S29 | S28  
1918

Statement of evidence relative to this corner location is on back of page.

311938

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

  
David S. Landecker  
Date 5-1-89 Registration No. 17008

OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 9:10 A. .M. on the 9 day of May A.D., 19 89

County Recorder Claudine Kayla  
By MS, Deputy

DOCUMENT NO. 311938

Statement of Evidence:

East Quarter Corner Section 29, Township 141  
North, Range 28 West, Cass County, Minnesota

T-9 141-28  
Bk.7 Pg.44

1874 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 28 West. The notes indicate a wood post was set to mark the corner position and the following witness: a 7 inch Poplar stub North 64 degrees West a distance of 40 links.

1917 County Surveyor's Record Book C page 67 show survey by Ben Clark. He set an iron monument.

1918 U.S. General Land Office dependant resurvey reestablished this corner proportionally. A 1 inch by 36 inch iron pipe with a marked brass cap was set to mark the corner. The following bearing trees were marked: a 6 inch Poplar North 23 and 3/4 degrees East a distance of 125 links; and a 6 inch Norway Pine North 6 and 1/2 degrees West a distance of 290 links.

1986 U.S. Forest Service crews set an aerial target over this corner position for determination of coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on November 4 a Landecker-Stevenson & Associates crew visited the corner and found the following evidence: a 1 inch General Land Office iron pipe with brass cap, the 1918 General Land Office Northwest Pine bearing tree now 20 inches. New bearing trees were marked as shown and steel sign posts are in place as noted on front of this certificate.