

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 13, Township 143N, Range 26W, 5th P.M.


STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

- On \_\_\_\_\_ found a \_\_\_\_\_  
DATE
- left monument as found,  lowered monument,  removed monument (explain)
- On 5-13-1990 placed a 2" X 54" brass capped monument  
DATE

Monument Marked

SKETCH OF REFERENCE TIES  
not to scale




*X* 7" Cedar  
N23°E 25.59

SEC. 12

*X* 12" Cedar  
N80°W 32.25

■ Steel Post  
North 4.3



6" Ash  
S70°E 36.74



SEC. 13

All trees are scribed, painted with a 30d bearings are true spike in side and USFS 54-3 tag.

Statement of evidence relative to this corner location is on back of page. 32 3157

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

William C. Osprey  
Date 8/22/90 Registration No. 17767

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 3:16 P. .M. on the 28 day of August A.D., 19 90

County Recorder Claudia Keyler

By MJ, Deputy

DOCUMENT NO. 32 3157

Statement of Evidence:

J23 North quarter corner section 13

1/4 Cor. 12 and 13 (N 1/4 Cor. Sec. 13)

- 1872 U.S. General Land Office survey set wood post for corner and the following references were noted:  
Spruce 4" S 32 degrees W, 10 Links ( 6.60 feet)  
Tamarack 8" N 51 degrees W, 18 Links (11.88 feet)
- 7-2-1964 Morrison and Morgan, USFS, corner card states found blue line painted E and W of corner, no brass cap of BT's, set approximate corner tag on 6" Aspen.
- 1969 Curt Krause, USFS, search area has been logged and heavily burned, no evidence of corner, or BT's found.
- 11-8-1989 Personnel from Kovanen & Osufsen Inc. chain to search area from section corner to west, area has been logged and burned, find no evidence of corner.
- 5-13-1990 Personnel from Kovanen & Osufsen Inc. made an additional search of area and set a 2" x 54" brass capped monument in lost position and the following witnesses:  
Cedar 12" N 80 degrees W, 32.25 feet  
Cedar 7" N 23 degrees E, 25.59 feet  
Ash 6" S 70 degrees E, 36.74 feet  
Set 8' steel sign post with sign attached, East  
4.1 feet  
Set 8' steel sign post with sign attached, North  
4.3 feet

This position is not traceable to the original GLO corner, but accepted as corner for lack of further evidence.