

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

West Quarter _____ Corner of Section 7, Township 142, Range 31, 5th P.M.


STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

- On 12/5/90 found a 2 inch iron pipe up 14 inches
DATE
- left monument as found, lowered monument, removed monument (explain)
- On 2/4/91 placed an aluminum cap on found 2 inch iron pipe
DATE

Magnetic Decl: 5° East SKETCH OF REFERENCE TIES
Not to Scale

All distances are horizontal to nail in side of tree.



9" White Pine
N 46 W 24.14'

10" Norway Pine
N 57 E 6.75'

Corner is located in ravine in small Norway and White Pine grove

8' steel sign post
Southerly 2.35'

8" White Pine
S 16 W 22.09'

Monument Stamped
T142N
R32W R31W
1/2
S12+57
1991
RLS 17008

All trees are scribed, painted with red enamel and marked with a 54-3 (bearing tree) tag.

Statement of evidence relative to this corner location is on back of page. 327266

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Alvin A. Oudek 3/6/91
SIGNATURE DATE

Registration No. 17008

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

OFFICE OF THE REGISTER OF DEEDS
County of Cass

I hereby certify that this document was filed in the Reg. of Deeds office at 2:15 P. .M. on the 11 day of March A.D., 19 91

Register of Deeds *Clairine K. Kaylor*
By *M. J.*, Deputy

DOCUMENT NO. 327266

West Quarter corner, Section 7, Township 142 North,
Range 31 West, Cass County, Minnesota

G-1 142-31

1871 George Stuntz, U.S. Deputy Surveyor, originally established this corner position while running the West line of Township 142 North, Range 31 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 7 inch Birch South 52 degrees West a distance of 11 links; and a 7 inch Birch South 85 degrees East a distance of 20 links.

1915 Cass County Surveyor's Record Book C, page 44, shows a survey by E.B. Horst. He set an iron monument at the original government distance from the Southwest corner of Section 7, on the west line of Section 7.

1915 County Resurvey in the Cass County Recorder's Office file cabinet E number 57 shows survey by John Curo. Found iron monument as set by Horst.

1988 United States Forest Service personnel locate iron pipe in traverse of West line of Township 142 North, Range 31 West.

1990 Landecker and Associates, Inc. survey crew locate 2 inch iron pipe, up 14 inches, in traverse of Section 7. The found iron pipe compares well with other corners found in Section 7 as shown on the 1915 Curo Resurvey plat. Landecker and Associates, Inc. accepts the found iron as the corner established and perpetuated by Horst and Curo in their 1915 surveys.

1991 on February 4, a Landecker and Associates, Inc. survey crew place an aluminum cap on found 2 inch iron pipe, up 14 inches. Monument is located in ravine in small Norway and White Pine grove. New bearing trees were marked as shown and a steel sign post set as noted on front of this certificate.