

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER


NORTH Corner of Section 8, Township 136, Range 30, 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

- On _____ found _____
- left monument as found, lowered monument, removed monument (explain)
- On 11/17/10 PLACED 1/2" x 16" Iron pipe capped #44530
DATE (set iron 0.5' below surface)

SKETCH OF REFERENCE TIES



NAD83 (1996 ADJUSTMENT)
CASS COUNTY SOUTH DATUM

N= 267,442.999
E= 494,671.614

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

[Signature]
SURVEYOR

2/10/11
DATE

Registration No. 44530

- Land surveyor,
- County Surveyor,

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the Co. Recorders office at ____M. on the _____ day of _____ A.D., 20__

County Recorder _____

By _____, Deputy

DOCUMENT NO. _____



Statement of Evidence:**North Quarter corner of Section 8, Township 136 North, Range 30 West**

Oct. 1870 R. Cronk, GLO Deputy Surveyor set a wood post for the original corner and referenced it as follows:

8" Birch N20°W 8 links (5.28 feet)
10" Birch S47°E 25 links (16.50 feet)

June 1909 Township Road Order shows no survey.

Nov. 2010 Craig E. Johnson, LS, CFedS, set a 1/2 iron pipe capped No. 44530, the corner was established by single proportion on line and mid way between the NW and NE corners of Section 8.

A000568460
OFFICE OF COUNTY RECORDER
CASS COUNTY MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON
02/23/2011 07:52:48 AM
AS DOC #: A000568460
PAGES: 2 REC FEES: 0.00
KATHRYN M. NORBY
COUNTY RECORDER