

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

EAST QUARTER Corner of Section 27, Township 135 N, Range 32 W

5TH Principal Meridian, State of Minnesota, County of CASS


At the corner location shown on the sketch:

■ On 12-8-11 found a 1/2 INCH O.D. REBAR 6 INCHES BELOW ROAD SURFACE  
DATE

left monument as found,  lowered monument,  removed monument (explain)

On \_\_\_\_\_ Placed a \_\_\_\_\_  
DATE

## SKETCH OF REFERENCE TIES



NOT TO SCALE  
MAGNETIC DECLINATION 6'E

NE COR.  
SEC. 27, T. 135N. R. 32W  
CASS COUNTY, MN

WOOD FENCEPOST  
SET SPIKE IN NORTHEAST FACE

8" INCH BURR OAK  
SET SPIKE IN NORTHWEST FACE  
MARKED WITH BLAZING

SECTION  
27  
PASTURE

WOODED PASTURE  
SECTION  
26

FOUND IRON PIPE  
MARKED WITH RLS 461165

WOOD CORNER POST  
SET SPIKE IN SOUTH FACE

COUNTY ROAD  
NO. 106

SE COR.  
SEC. 27, T. 135N. R. 32W  
CASS COUNTY, MN

BEARINGS ARE BASED ON  
CASS COUNTY COORDINATE SYSTEM,  
SOUTH ZONE. NAD 83 1996 ADJ.

CASS COUNTY  
COORDINATE SYSTEM - SOUTH ZONE  
NAD 83 1996 ADJ.  
N = 217243.60  
E = 442145.43

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

[Signature] 3/1/2012  
Signature Date

License No. 17768

- Land Surveyor  Professional Engineer
- County Surveyor  County Engineer

OFFICE OF THE COUNTY RECORDER  
County of CASS

I hereby certify that this document was filed in the County Recorders office at \_\_\_\_\_ M. on the \_\_\_\_\_ day of \_\_\_\_\_ A.D., 20\_\_\_\_  
County Recorder \_\_\_\_\_  
By \_\_\_\_\_, Deputy

DOCUMENT NO. \_\_\_\_\_

**East Quarter Corner, Section 27, Township 135 North, Range 32, Cass County, MN**

- 1866 Oscar E. Garrison, GLO Deputy Surveyor, set post with two bearing trees for this corner. Reference ties: 18 inch Yellow Pine N 51 ½ degrees East .26 chains; 22 inch Yellow Pine S 74 ½ degrees West .66 chains.
- 1900 Byron Township Supervisors Road Order. Road survey along the East-West Quarter line of said Section 27. No mention of this corner.
- 12/2011 Arro Land Surveyors search the area for the GLO reference ties and post and found nothing. There was a fence line east and a north-south county road for occupation.
- 12/2011 Arro Land Surveyors found an ½ inch OD rebar 6 inches below the surface and in line with the fence line to the east and within the road bed of the county road. The found monument was in harmony with the occupation and with the measurements from the original survey. The found monument was accepted to mark the corner.



**A000578695**  
**OFFICE OF COUNTY RECORDER**  
**CASS COUNTY MINNESOTA**  
**CERTIFIED, FILED, AND/OR**  
**RECORDED ON**  
**03/15/2012 10:27:24 AM**  
**AS DOC #: A000578695**  
**PAGES: 2 REC FEES: 0.00**  
**KATHRYN M. NORBY**  
**COUNTY RECORDER**