



Statement of Evidence

Northeast corner of Section 12, Township 139 North, Range 25 West, 5th Principal Meridian on the 3rd Guide Meridian.

- 1863 The US General Land Office, in the notes of the 3rd Guide Meridian between the 9th and 10th Parallels, set a post for the original corner and referenced it as follows:
 20" W. Pine S 35° W 31 links 14" Aspen N 10° W 16 links
 Said records are on file with the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the Cass County Surveyor's Office (CCSO).

- 1911 J.W.Curo, LS 1428, Cass County Surveyor, Survey Record 162, Book A, page 351, on file in the CCSO, states "we find the stump of the S.W. pine plainly marked from which we set the true corner." Page 352 shows a section corner in place listed as a wood post.

- 1937 The CCC Washburn Lake field book 1, page 10, on file at the DNR office in Brainerd, indicates an approximate corner was set 80 chains from the south.

- 1937 The CCC Washburn Lake field book 2, page 46, on file at the DNR office in Brainerd, indicates a found old 3" Aspen stake and the stump of W. Pine B.T. S 31 W 22.2' a 4" stake 5' high with yellow tag was set.

- 1937 The CCC Washburn Lake field book 7 (KLJ could not confirm book number. Book 7 does not contain records in this township) on file at the DNR office in Brainerd, indicates a W. Pine stump was located at S 30°30' W 20.4' with a blaze. A 1 1/2" x 54" I.P. was set 2 1/2' in ground with a scribed 2 1/4" cap. The following references were noted:
 W. Pine stump S 30 1/2° W 20.4
 6.4" Balsam scribed T139N R25W S 12 B.T. S 36° W 40 feet

- 1937 The CCC Washburn Lake field book 20, on file at the DNR office in Brainerd, indicates a road is 1340' south of a found iron pipe.

- 2004 B.Hippen, CCSO technician, records of the CCSO, found a 1 1/2 inch outside diameter iron pipe, with a screw on cap (CCC), up 2.5 feet, and add the following witnesses:
 7" Maple North 35.15 feet 10" Balsam N 85° E 6.70 feet
 5" Maple S 10° W 23.15 feet *distances are measured to a double head nail

- 2013 A KLJ survey crew found a 1 1/2" iron pipe, and is witnessed with the ties shown on the front of this certificate. Jarrett Leas, RLS #42619, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.