



Statement of Evidence

Northeast corner of Section 29, Township 139 North, Range 26 West, 5th Principal Meridian.

- 1863 The US General Land Office, in notes of the subdivision of Township 139 North, Range 26 West, set a post for the original corner and referenced it as follows:
- | | | | | | |
|-------------|---------|-----------|-------------|---------|-----------|
| 20" N. Pine | N 45° E | 100 links | 20" N. Pine | N 8° W | 106 links |
| 20" N. Pine | S 30° E | 130 links | 30" N. Pine | S 60° W | 35 links |
- Said records are on file with the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the Cass County Surveyor's Office (CCSO).
- 1910 A.W. Moulster, Deputy County Surveyor, Curo field book 48_1, page 75, indicates a search was made finding no evidence of the original corner or BT's, stating, "After hunting several hours for the BT's we gave up".
- 1987 Walter Curo, LS 11395, Curo field book 315, page 63, a sketch illustrates an iron monument found.
- 2013 Jarrett Leas, LS 42619, March 2013, in correspondence with Mr. Buckler by telephone, determined the corner was set by Mr. Buckler circa mid 1980's.
- 2013 A KLJ survey crew found a ½" iron pipe flush with ground, and is witnessed with the found ties shown on the front of this certificate. Jarrett Leas, RLS #42619, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.