

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 2

Township 139 N , Range 25 W , 5th P.M.

STATE OF MINNESOTA, COUNTY OF Cass



**A000600789**

**OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON**

**3/6/2014 11:51:17 AM**

**AS DOC #: A000600789**

**PAGES: 2**

**REC FEES: 0.00**

**KATHRYN M. NORBY  
CASS COUNTY RECORDER**

BY SR Dep


On \_\_\_\_\_, found a(n): \_\_\_\_\_  
DATE

- left monument as found
- lowered monument
- removed monument (explain)
- raised monument


On 4/29/2013, set a(n): 5/8"x 24" Rebar With Plastic Cap  
DATE  
Stamped "Leas MN 42619". Up 0.5'

See "Statement of Evidence" for further details (on back)

(reserved for recording data)



2 | 1



"SKETCH OF REFERENCE TIES"  
(not to scale - bearings are magnetic)

Ties are measured to center of monument unless otherwise noted.

UNITS =  Metric  English

CASS COUNTY SOUTH COORDINATES

Northing: 365544.89

Easting: 667621.59

NAD 83/2007 Adjustment.  
Obtained by RTK GPS observations.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

signature  
Jarrett M. Leas, Minnesota License No. 42619

2-27-14  
date



Statement of Evidence

**East Quarter corner of Section 2, Township 139 North, Range 25 West, 5th Principal Meridian.**

1863 The US General Land Office, in notes of the subdivision of Township 139 North, Range 25 West, set a post for the original corner and referenced it as follows:

6" W.Birch East 23 links                      6" Red. Oak N 6° W    13 links

Said records are on file with the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the Cass County Surveyor's Office (CCSO).

2013 KLJ field crews searched the area and find no evidence of the corner or accessories. This corner was set lost by proportioning between the NE 2 and the NE 11. A 5/8" x 24" rebar with plastic cap stamped "Leas MN 42619" was set to mark the corner position and is witnessed with the ties shown on the front of this certificate. Jarrett Leas, RLS #42619, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.