

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 33  
Township 145 N, Range 28 W, 5th P.M.  
STATE OF MINNESOTA, COUNTY OF CASS



**A000601878**

OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON

4/24/2014 11:39:34 AM

AS DOC #: **A000601878**

PAGES: **2**

REC FEES: **0.00**

**KATHRYN M. NORBY**  
CASS COUNTY RECORDER

BY SR Dep

On 04/01/2010, found a(n): 3" Brass Cap On 2" Pipe 1.5'  
DATE  
Above Ground, Set By RLS# 12261 In 1978

- left monument as found
- lowered monument
- removed monument (explain)
- raised monument

On \_\_\_\_\_, set a(n): \_\_\_\_\_  
DATE

See "Statement of Evidence" for further details (on back)

(reserved for recording data)

8" Birch KLJ Set New  
Bearing Tag, Nail & Disk  
1' Up On North Face

U-Post With 1978  
Forest Service Sign

West  
3.0'

3" Brass Cap On 2" Pipe  
1.5' Above Ground, Set By  
RLS# 12261 In 1978


16" Norway Pine With 1978  
Blaze On Northwest Face 1'  
Up, And Bearing Tag 54-3

24" Norway Pine With 1936  
Blaze & Bearing Tag On  
Northwest Face 6' Up

28

33

### "SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)



Ties are measured to center of monument  
unless otherwise noted.

UNITS =  Metric  English

UTM COORDINATES, ZONE 15

Northing: 17203619.370

Easting: 1334111.823

NAD 83/1996 Adjustment.

Obtained by RTK GPS observations.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Ross Wamre  
signature

6/24/12  
date

Ross Wamre, Minnesota License No. 45334



**STATEMENT OF EVIDENCE:** Quarter Corner common to Sections 28 and 33 of Township 145 North,  
Range 28 West of the 5<sup>th</sup> Principal Meridian

**1873;** This corner was originally established by P.H. Conger his field notes indicate a post set at this corner position, witnessed by:

Jack Pine 8" North 5 links  
Jack Pine 6" South 10<sup>o</sup> East, 40 links

**1936;** J.A. Gjelhaug, RLS #1337, CCC, USFS Book 1 of Township 145 North, Range 28 West, page 33, survey for the Boulder Hill Lookout Tower, set an oak post in and one of the original BTs. Information is on file with the USFS Cass Lake office.

Jack Pine (stump) North 5 links (3.3') (1873 tie)  
Jack Pine (windfall & rotted) South 10<sup>o</sup> East, 40 links (26.4') (1873 tie)  
Norway Pine 14" South 32<sup>o</sup> East, 30 links scribed ¼ S 33 BT

**1978;** Milo Stefan, RLS #12261, USFS Book 1 of Township 145 North, Range 28 West, page 33, found a 4" square x 24" high pine post. To perpetuate the corner he set a 2" dia. x 5' long galvanized steel pipe with concrete inside and capped with a 3" dia. stamped brass cap next to the pine post and witnessed.

Norway Pine 23" South 32<sup>o</sup> East, 19.8' ¼ S 33 (1936 tie) re-scribed  
4" square x 24" high pine post (1936 tie)  
J. Pine 12" North 79<sup>o</sup> East, 11.47' mrkd ¼ S 28 BT  
N. Pine 12" South 41<sup>o</sup> East, 44.44' mrkd ¼ S 33 BT  
N. Pine 9" South 2<sup>o</sup> West, 60.60' mrkd ¼ S 33 BT  
8' Steel Post Due West 2.3' With F.S. Sign 54-4

**2004;** R. Main, USFS Book 1 of Township 145 North, Range 28 West, page 33, found iron, collected a GPS position on its location and observed BTs.

**2010;** A KLJ survey crew found a 3" Brass Cap on a 2" galvanized iron pipe 1.5' above ground and three accessories. Witnesses found and established on front face of this certificate.

**2012;** Ross Wamre, RLS #45334, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.

Contacts pertaining to this corner are as follows:

Cass County Recorder's Office  
Cass County Engineers Office  
Cass County Surveyors Office  
Northern Engineering and Consulting Inc.  
United States Forest Service  
MnDOT – District Office 2  
Bureau of Indians Affairs – Bemidji  
Bureau of Land Management's (BLM) Northeastern States Field Office