

Statement of Evidence**North Quarter corner of Section 11, Township 140 North, Range 27 West, 5th Principal Meridian.**

- Dec. 1873 F.G. Winston, General Land Office (GLO) Deputy Surveyor, notes for the subdivision of Township 140 North, Range 27 West, set a post for the original corner and referenced it as follows:
 8" R. Oak N 70° E 10 links (6.60 feet) 6" R. Oak S 71° W 42 links (27.72 feet)
 The above record is on file with the Minnesota Historical Society in St. Paul, Minnesota, copies are filed with the Cass County Highway Department, Surveyor's Office (CCHD/SO).
- April 1910 A.W. Moulster, LS 967, Deputy Cass County Surveyor, Curo Book 48-1, page 44 to 45, on file in the CCHD/SO, states "hole where old post was – old stumps stand as follows":
 Old stump N 70° E 6.90 feet Stump S 71° W 17.3 feet
- 1963 Cass County Highway Department (CCHD), S.P. 11-607-02, on file in the CCHD, plan indicates subject corner assumed at Station 426+65.
- Dec. 2006 B.W. Skipton, LS 17768, unrecorded Certificate of Location, on file in the CCHD/SO, indicates a 1/2 inch by 14 inch iron pipe was set at the lost position and witnessed as follows:
 10" Maple N 55° W 78.08 feet 5" Maple N 8° W 51.72 feet
 12" N. Pine S 25° E 63.01 feet
- June 2011 B. Hippen, technician, records of the CCHD/SO, found a 7/8 inch outside diameter iron pipe, capped RLS 17768, 1.5 feet, more or less, North of centerline CSAH # 007.
- Aug. 2011 B. Hippen, technician and P. Swentkofske, CCHD equipment operator, records of the CCHD/SO, prior to reconstruction of CSAH # 007, excavated a 20 foot east-west by 10 foot north-south area based on record dimensions. The dig was 8 feet deep to natural soil. Pieces of charred wood and a dark ring, vertical for 0.4 foot, was recovered down 7.5 feet.
- Oct. 2011 B. Hippen, technician, records of the CCHD/SO, set a 1 inch by 30 inch aluminum tube with aluminum cap at the dark ring location which fit well with the mid point between the recovered Northeast and Northwest corners of Section 11, flush, 3 feet, more or less North of new centerline of CSAH # 007 and witnessed as follows:
 10" R. Oak N 45° W 76.52 feet 5" R. Oak North 49.68 feet
 12" N. Pine S 20° E 65.01 feet

The recovered and established witnesses for this corner position are shown on the face of this document.

Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument set in 2011 by the CCHD/SO, is the correct perpetuation of this corner.

County Coordinates (Cass County North)

Northing 158183.80

Easting 538924.29