

**Index No. N.0-05.0**Statement of Evidence**Northeast corner of Section 19, Township 139 North, Range 28 West, 5th Principal Meridian.**

- April 1864 Johnson and Thornton, General Land Office Deputy Surveyors, notes for the subdivision of Township 139 North, Range 28 West, set a post for the original corner and referenced it as follows:
 16" Y. Pine N 80° E 16 links (10.56 feet) 18" Y. Pine N 15° W 83 links (54.78 feet)
 18" W. Pine S 40° E 47 links (31.02 feet) 20" Y. Pine S 55° W 28 links (18.48 feet)
 The above record is on file with the Minnesota Historical Society in St. Paul, Minnesota, copies are filed with the Cass County Highway Department, Surveyor's Office (CCHD/SO).
- Dec. 1919 B.F. Clark, LS 231, CCHD/SO, Survey Record, Book C, Record No. 434, page 333, on file in the CCHD/SO, states "Then went to the Sec. cor. 17-18-19-20 and set iron pipe with hardwood point 1 ½ ft long drove same 3 ½ ft.in ground. Where lines intersect on a double proportion". Lists witnesses as follows:
 5" Norway N 26° W 27.3 feet 10" J. Pine N 60° E 40.7 feet
 5" Norway S 35° E 46.1 feet
- Dec. 1919 Blind Lake Township Final Road Order, states a road Beginning at South West corner of section 20 Township 139 Range 28 thence North 2 miles to South East corner of Section 7.
- Dec. 1921 B.F. Clark, LS 231, CCHD/SO, County Resurvey Plat, on file in the Cass County Recorders Office, as Document Number 69797, indicates Iron Monument.
- Dec. 1926 Blind Lake Township Final Road Order, Surveyor's Report and Plat indicates a road from the north quarter corner of section 19 to the northeast corner of section 20.
- 1938 Civilian Conservation Corps, personnel, Washburn Lake Book 12, page 22, on file in the Minnesota Department of Natural Resources, Outing Office, state at 5280' from E -- set Approx cor.
- Aug. 1975 L. Mengis, technician, Cass County Highway Department(CCHD) S.A.P. 11-649-01, on file in the CCHD, plan indicate a 2 inch I.P. for corner, on centerline at station 243+00.7. Notes indicate the following witnesses:
 14" N. Pine SSE 98.2 feet 6" Pop. NE 87.0 feet
 20" N. Pine NW 75.3 feet
- Feb. 2003 B. Hippen and T. Anderson, technicians, records of the CCHD/SO, found a 60d spike, down 0.8 foot, on centerline of County Road #49 and witnesses as follows:
 16" N. Pine S 15° E 98.51 feet(1975) 10" Maple S 40° W 121.78 feet
 16" N. Pine N 12° W 84.76 feet
- July 2014 B. Hippen, technician, records of the CCHD/SO, found 60d spike, down 0.6 foot, on centerline of County Road #49 prior to reconstruction and the 2003 witnesses in good condition.
- Sept. 2015 B. Hippen, technician, records of the CCHD/SO, set an aluminum Cass County monument in place of the 60d spike, on the new centerline of County Road #49 and witnessed as follows:
 18" N. Pine S 15° E 98.51 feet(1975) 10" Maple S 40° W 121.78 feet
 18" N. Pine N 12° W 84.76 feet

The monument, recovered and established references for the position are shown on the face of this document.

Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument set by CCHD/SO in 2015 is the accepted location of this corner.

County Coordinates (Cass County North)
 Northing 116330.09
 Easting 489357.54