



A000676173

OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON

8/27/2021 11:47:00 AM

AS DOC #: A000676173

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY  
CASS COUNTY RECORDER

BY KF Dep TX#: 174777

I HEREBY CERTIFY THAT THIS DOCUMENT AND THE DATA  
CONTAINED HEREIN WAS PREPARED BY ME OR UNDER  
MY DIRECT SUPERVISION.

Guy T. Carlson  
GUY T. CARLSON

8/29/2021  
DATE

LICENSE NO. 40991

- LAND SURVEYOR       PROFESSIONAL ENGINEER
- COUNTY SURVEYOR     COUNTY ENGINEER

NAD 1983 (1996 HARN) CASS COUNTY NORTH ZONE COORDINATES  
N= 284478.549 E= 586081.174 US SURVEY FT  
(COORDINATES ARE SHOWN AS INFORMATION ONLY, SUBJECT TO VERIFICATION)

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

INDEX NO. E-07, NORTH QUARTER CORNER OF SECTION 8, TOWNSHIP 144, RANGE 25, 5TH P.M.  
STATE OF MINNESOTA, COUNTY OF CASS

AT THE CORNER LOCATION SHOWN ON THE SKETCH:


- ON 7/16/2021 FOUND A(N) UNITED STATES FOREST SERVICE, ALUMINUM CAPPED, ALUMINUM ROD MONUMENT.  
DATE
- LEFT MONUMENT AS FOUND,       LOWERED MONUMENT,       REMOVED MONUMENT (EXPLAIN)
- ON \_\_\_\_\_ PLACED A(N) \_\_\_\_\_  
DATE

## SKETCH OF REFERENCE TIES

DECLINATION 0°  
SKETCH NOT TO SCALE



MONUMENT MARKED:



10 1/2" TAMARACK WITH A 60d SPIKE AND WASHER IN THE BASE. A TAG IS AFFIXED.

T144-R25-S5

14" SPRUCE WITH A 20d NAIL IN THE BASE. ESTABLISHED 1984.

WOODS

WOODS

8' STEEL POST WITH USFS 54-9 SIGN ATTACHED.

2.60'  
N70°W

WOODS

WOODS

8" ASPEN WITH A 60d SPIKE AND WASHER IN THE BASE. A TAG IS AFFIXED.

T144-R25-S8

STATEMENT OF EVIDENCE RELATIVE TO THIS CORNER LOCATION IS ON BACK OF PAGE



**STATEMENT OF EVIDENCE:** Quarter Corner of Sections 5 and 8, Township 144 North, Range 25 West, of the 5th Principal Meridian.

1876; This corner was originally established by B.C. Baldwin, Deputy Surveyor under contract to the General Land Office (GLO), now the Bureau of Land Management (BLM). A copy of the plat of this township and hand copied field notes are on file in the Itasca County Surveyor's Office. These Field notes indicate a wood post was set to mark this corner position, which was witnessed by:

Tamarack,	6",	North 35° East,	15 links,	9.90 feet;
Tamarack,	4",	South 56° West,	6 links,	3.96 feet:

1985; (January) James Parker, LS 9235, of Advance Surveying under a United States Forest Service contract, performed a Dependent Resurvey of this Township. He failed to find any evidence of this corner position. He set a 5/8" by 5' long aluminum rod with a 3" stamped aluminum cap at a proportioned position between the southeast and southwest corners of Section 5. He filed a Certificate of Location of Government Corner with the Cass County Recorder. See Document #281669. This corner position was witnessed by:

Spruce,	3",	North 55° East,	51.58 feet;
Aspen,	6",	South 55° East,	30.79 feet:

2021; (July) Itasca County Department of Surveying and Mapping personnel T. Lasecki and W. Storm recovered the monument as set in 1985 up 15". Its position was verified by the recovered 1985 Spruce witness tree. The 1985 Aspen is now on the ground. The monument was driven flush with the ground and geodetic coordinates were collected on the monument. Township 144-25 Township Field Book 1, page 37. The recovered and established witnesses are as shown on the face of this document.

