

Statement of Evidence: Meander Corner to Sections 5 and 8, Township 141 North, Range 31 West, 5th Principal Meridian. East side of Fifth Lake.

1873 P.H. Conger, U.S. Deputy Surveyor, set a post for this Meander Corner in his subdivision of the Township between August 5, 1873 and August 30, 1873. As references he scribed:

Birch	3 inch	S21°E	21 links (13.86 feet)
Birch	8 inch	N84°E	85 links (56.1 feet)

1917 E.B. Horst, Cass County Surveyor, found the original Northeast BT and set a 2 inch by 48 inch iron monument. No new ties were mentioned. in County Book "C" page 123-124.

1962 Peter J. Meyer, R.L.S., with the U.S.F.S. found existing monument and the original Northeast BT used by Horst, now a 14 inch Birch stub 6 feet high with blaze facing corner. Meyer replaced existing monument with a 2½ inch (O.D.) x 5 foot long iron pipe with 3 inch diameter brass cap. He then established the following ties:

Red Pine	22 inch	S2°W	86.4 feet
6 foot steel post		S60°E	5.23 feet

1984 C. Krause with U.S.F.S. found iron monument tipped and straightened. He set a 8 foot steel post for a reference, S55°E, 5.30 feet.

1984 Kelly M. Booge, under F.S. Contract No. 53-6392-4-00996, made a thorough search for physical evidence of this corner on August 30 and found monument set by Krause with existing references as follows:

Norway Pine	24 inch	S6°W	85.30 feet
8 foot steel post		S55°E	5.30 feet

Booge then established additional references as shown on the sketch.

This Certificate was made to update the 1962 Certificate, Document No. 92, in book of Corner Certificates in Cass County Recorder's Office.

Kelly M. Booge is an employee of Okerman Surveying, Inc.