

Statement of Evidence:

Northeast Corner Section 28, Township 141
North, Range 29 West, Cass County, Minnesota

R-13 141-29
Bk.4 Pg.35

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 29 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 12 inch White Pine North 2 degrees East a distance of 43 links; an 18 inch White Pine North 23 degrees West a distance of 18 links; a 24 inch Yellow Pine South 21 links West a distance of 14 links; and an 18 inch White Pine South 24 degrees East a distance of 56 links.

1912 County Surveyor's Record Book A pages 500-502 show survey by John Curo. He found stumps of all 4 of the original bearing trees; set a 3 by 3 by 36 inch Oak stake in place of old stake. New bearing trees were marked: a 3 inch Poplar South 16 degrees 50 minutes East a distance of 45.00 feet; a 3 inch Poplar South 55 degrees 46 minutes West a distance of 19.4 feet; a 4 inch Oak North 56 degrees West a distance of 18.5 feet; and a 30 inch White Pine stump North 22 degrees 08 seconds East 48.75 feet.

1918 U.S. General Land Office dependant resurvey found the corner marked by remains of wood stake and stumps of Northwest, Southwest and Southeast bearing trees. A 2 inch by 36 inch iron pipe with a marked brass cap was set to mark the corner. The following bearing trees were marked: a 6 inch Black Oak South 12 degrees 15 minutes East a distance of 119 links; a 6 inch Birch South 73 degrees 15 minutes West a distance of 118 links; and a 5 inch Black Oak North 55 degrees 30 minutes West a distance of 28 links.

1965 U.S. Forest Service records show the following: found the 2 inch General Land Office brass cap monument and two 1918 bearing trees: an 11 inch Oak South 12 degrees East a distance of 78.54 feet; and a 21 inch Black Oak North 55 degrees West a distance of 18.48 feet. New bearing trees were marked: a 21 inch Oak North 55 degrees West a distance of 18.48 feet; an 11 inch Oak South 12 degrees East a distance of 78.54 feet (rescribed); a 6 inch Oak North 18 degrees East a distance of 29.3 feet; and an 18 inch Oak South 15 degrees West a distance of 21.1 feet.

1986 U.S. Forest Service crews set an aerial target over this corner position for determination of coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner Section 28, Township 141
North, Range 29 West, Cass County, Minnesota

1988 on June 10 a Landecker-Stevenson & Associates crew visited the corner and found the following evidence: a 2 inch brass cap monument in good condition; partly decayed stump of original Pine bearing tree South 21 degrees West a distance of 9 feet; and a 2 foot high stump of 1918 bearing tree North 55 degrees West a distance of 18.4 feet; and a 3 foot high stub of 1918 bearing tree South 12 degrees East a distance of 78.5 feet; and a 4 foot high stub of 1965 Oak North 18 degrees East a distance of 29.3 feet; and the 3 foot high stump of 1965 Oak South 15 degrees West a distance of 21.1 feet. New bearing trees were marked and steel sign post set as shown on front of this certificate.