

Statement of Evidence:

North Quarter Corner Section 32, Township 141
North, Range 29 West, Cass County, Minnesota

V-7 141-29
Bk. 4 Pg. 60

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 29 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 24 inch White Pine North 81 and 1/2 degrees East a distance of 42 links; and a 30 inch White Pine South 45 degrees West a distance of 51 links.

1966 U.S. Forest Service records show the following: technician Ekstrom chained to area from the Northwest Corner Section 32. He found a new post marked temporary Quarter Corner, no evidence of original bearing trees.

1974 Myron Landecker, Registered Land Surveyor Number 7452, surveyed the plat of ONDARKO'S MOCCASIN LAKE ACRES. In his determination of the subdivision of Section 32, he determined this corner lost and computed a corner midway between the Northwest and Northeast corners of this section.

1980 Walt E. Curo, Registered Land Surveyor Number 11395, surveyed the plat of MOCCASIN BAY. In his determination of the subdivision of Section 32, he determined this corner lost and computed a corner midway between the Northwest and Northeast corners of this section.

1986 U.S. Forest Service crews set an aerial target in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on July 8 a Landecker-Stevenson & Associates crew searched for the corner. The following information was found and noted: several Pine stumps South, West, and Northwest from search position; none fit together for original and no evidence of post. The post found in 1966 is South 18 degrees West a distance of 80.2 feet from target and is South 27 degrees West from the corner established in this survey.

1988 on December 1 a Landecker-Stevenson & Associates crew set a 2 inch by 48 inch iron pipe with brass cap, plastic base and magnet at the lost, single proportion position between the Northwest and Northeast corners of Section 32. New bearing trees were marked as shown and steel sign posts set as noted on front of this certificate.