

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter _____ Corner of Section 31, Township 141 N, Range 29 W, 5th P.M.

STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch: Latitude: 46° 59' 37.693"
 Longitude: 94° 23' 47.161"

- On _____ found a _____
DATE
- left monument as found, lowered monument, removed monument (explain)
- On 1/24/89 placed a 2" by 54" iron pipe with brass cap and
DATE
plastic base with magnet.

Magnetic Decl: 5° East SKETCH OF REFERENCE TIES
 Not to Scale

All distances are horizontal to nail in side of tree.



 11" Birch
 N 52 W 61.08'

 26" Norway Pine
 S 75 E 87.99'

 19" Norway Pine
 S 6 W 89.76'


Monument is located in hardwoods with scattering of large Norway Pine, 190' Easterly of Stocking Lake. 8' steel sign post East 5.0'

Monument Stamped
 T 141 N R 29 W
 1/4 S30
 S31
 1989
 RLS 17008

All trees are painted with red enamel and marked with a 54-3 (bearing tree) tag.

Statement of evidence relative to this corner location is on back of page. 311852

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.


 David S. Landecker

Date 4-28-89 Registration No. 17008

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 4:00 P.M. on the 3 day of May A.D., 1989

County Recorder Claudia Kaye

By MJ, Deputy

DOCUMENT NO. 311852

Statement of Evidence:

North Quarter Corner Section 31, Township 141
North, Range 29 West, Cass County, Minnesota

V-3 141-29
Bk.6 Pg.46

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 29 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 5 inch Birch North 33 degrees East a distance of 56 links; and a 6 inch Burr Oak South 79 degrees East a distance of 62 links.

1986 U.S. Forest Service crews set an aerial target in the vicinity of this corner for the search and establishment of the true corner position. The target having coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner.

1988 on July 7 a Landecker-Stevenson & Associates crew searched for the corner. The following information was found and noted: no evidence of original post or accessories. This corner was determined lost.

1989 on January 24 a Landecker-Stevenson & Associates crew set a 2 inch by 54 inch iron pipe with brass cap and plastic base with magnet at the lost, single proportion position between the Northwest and Northeast corners of Section 31. New bearing trees were marked as shown and a steel sign post is in place as noted on front of this certificate.