

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 1, Township 143N, Range 26W, 5th P.M.

STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

- On _____ found a _____
DATE
- left monument as found, lowered monument, removed monument (explain)
- On 10-27-1989 placed a 2" X 48" brass capped monument
DATE


Monument Marked

SKETCH OF REFERENCE TIES not to scale

T144N R26W
S36
N-1/4
S1
T143N
1989
RLS 17767

 7" Maple
N15°E 32.64

SEC. 36



14" Balsam 
S75°W 15.94

 Steel Post
South 4.0

SEC. 1

 8" Maple
S23°W 37.30

bearings are true All trees are scribed, painted with a 30d spike in side and USFS 54-3 tag.

Statement of evidence relative to this corner location is on back of page. 323147

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

William C. Danjen

Date 8/22/90 Registration No. 17767

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 3:06 P. M. on the 28 day of August A.D., 19 90

County Recorder Claudia Kaylor

By MS, Deputy

DOCUMENT NO. 323147

Statement of Evidence:

A23 North quarter corner section 1

1/4 Cor. 1 and 36 (N 1/4 Cor. Sec. 1)

- 1872 U.S. General Land Office survey set wood post for corner and the following references were noted:
W. Pine 10" S 51 degrees E, 10 Links (6.60 feet)
W. Pine 12" N 33 degrees E, 8 Links (5.28 feet)
- 1962 A USFS approximate corner tag was placed on Oak tree in area.
- 10-24-1989 Personnel from Kovanen & Osufsen Inc. search area, find 1962 approximate corner tag, approx. 38 feet West of search position, no other evidence of corner is found.
- 10-27-1989 Personnel from Kovanen & Osufsen Inc. set a 2" x 48" brass capped monument by single proportion measurement and on line, between the Northwest corner of Section 2 and the Northeast corner of Section 1, witnesses are as follow:
Balsam 14" S 75 degrees W, 15.94 feet
Maple 7" N 15 degrees E, 32.64 feet
Maple 8" S 23 degrees W, 37.30 feet
Set 8' long steel sign post with sign attached, East 4.0 feet
Set 8' long steel sign post with sign attached, South 4.0 feet

This position is not traceable to the original GLO corner, but accepted as corner for lack of further evidence.