

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 27, Township 142N, Range 26W, 5<sup>th</sup> P.M.

STATE OF MINNESOTA, County of Cass


At the corner location shown on the sketch:

- On 11/30/94 found a Nothing  
DATE
- left monument as found,  lowered monument,  removed monument (explain)
- On 1/10/95 placed a 2 1/2" Dia. x 48" Galvanized iron monument with a 3" Dia. Brass Cap - 4" above ground.  
DATE

MAGNETIC: 2° E. DECL.

SKETCH OF REFERENCE TIES  
NOT TO SCALE


BRASS CAP MARKED:



## SECTION 22

SMALL POTHOLE SWAMP

7" ASH  
N 47° W - 27.80 Ft.  
TO A 20d NAIL ON  
SW SIDE 16" ABOVE  
GROUND. SCRIBED  
1/4 S22, BT.



7" ASH  
N 42° E - 23.73 Ft. TO A 20d  
NAIL ON NW SIDE 12" ABOVE  
GROUND. SCRIBED 1/4 S22, BT.

8' STEEL SIGNPOST  
W/SIGN 54-9 EAST-5.15 Ft.



9" MAPLE  
S 61° E - 14.69 Ft. TO A 20d  
NAIL ON N. SIDE 12" ABOVE  
GROUND. SCRIBED 1/4 S27, BT.

## SECTION 27

ALL BEARINGS ARE TRUE.  
ALL DISTANCES ARE HORIZ. AND TEMP CORRECTED.  
ALL TREES MARKED WITH RED ENAMEL PAINT AND WITH A 54-3 (BEARING TREE) TAG.

Statement of evidence relative to this corner location is on back of page.

365502

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Lowell G Schellack*

Date 3/21/95 Registration No. 15572

OFFICE OF THE COUNTY RECORDER  
County of CASS

I hereby certify that this document was filed in the Co. Recorders office at 2:30 P.M. on the 21<sup>st</sup> day of MARCH A.D., 19 95

County Recorder Claudia Kaylar

By N.O., Deputy

DOCUMENT NO. 365502

**Statement of Evidence:** NORTH QUARTER CORNER OF SECTION 27, TOWNSHIP 142 NORTH,  
RANGE 26 WEST OF THE 5<sup>th</sup> PRINCIPAL MERIDIAN.

The original public land survey was run in 1872 by Griffin. A post was set to mark the corner and two bearing trees were marked and recorded as accessories; A 6" maple that bears S55°E-12 links(7.92 feet); and a 5" Y. Birch that bears N12°W-11 links (7.26 feet). The notes of this survey are on file in the office of the Secretary of State, St. Paul, MN.

In the spring of 1963, McDonald and Ekstrom, USFS survey technicians, chained west from the northeast corner of Section 27 and found no evidence of the corner. Reported by W. Okerman. ~~Cass County Survey~~ Book #1, Page 54, USFS, Cass Lake, MN.  
USFS Corner

On November 29, 1994 Tom Miller, RLS and Jon Larson of Schellack Engineering and Land Surveying were at the corner location. A search area was established by traversing cardinal west from the northeast section corner, 2640 feet, the record bearing and distance. A four foot diameter hole was dug and no evidence of the corner was found and no accessories were found. A 1 5/8" I.D. x 48" long iron pipe up 30" was found approximately 65 feet north of the search location. No record is available as to who set the corner. A local surveyor, Walt Curo, was later contacted but he said he never set the corner.

On November 30, 1994 Lowell Schellack, RLS, Miller, and Larson revisited the corner location to conduct additional search. The iron pipe was found to set on the west edge of a small swamp. A dead and down tree, badly decayed, was found at the approximate location of the original maple bearing tree. A 2 foot section was cut out for identification. It was taken to the DNR in Park Rapids for identification. They said it is not a maple and is a conifer of some type. The position of the 1 5/8" iron pipe is about 1½ degrees off a cardinal direction. It is felt that the iron pipe is not a perpetuation of the original north quarter corner location.

After analysis of the above information, it was decided to re-establish the corner at the lost position between the northeast section corner and MC #31 on the east shore of Little Sand Lake. Calculations revealed a bearing and distance of N89° 26' 16.3"W - 2621.27 feet as compared to a record of west - 2640 feet. Our distance measurement is short of the original but is consistent with other measurements around the section being short of the record. USFS Contract, 1994-95

For additional information, contact the Cass County Surveyor's Office in Walker, MN.