


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Meander Corner on the south shore of Knights Lake, common to Sections 13 and 14, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota. June, 1997; Northern Lights Surveying and Mapping, Inc. perpetuated this corner, which had an intact Civilian Conservation Corps (C.C.C.) bearing tree and a Cass County pipe, with a galvanized steel pipe with a brass cap.

SKETCH OF REFERENCE TIES & EVIDENCE

T.142N., R.26W.



NOT TO SCALE

Bearings are Grid North, Minnesota Central Zone, measured with a hand compass adjusted to 3° East declination.

0.091m Ash
N11°W
11.800m to 20d nail
in east face
up 0.734m
scribed XX

0.490m Norway Pine
N48°W
4.440m to 20d nail
in face
up 0.260m
scribe overgrown
(1939)

Steel Signpost
East
1.082m
sign 54-9
(1997)


Meander Corner
Galvanized
Steel Pipe
Stamped
Brass Cap
(1997)

0.142m Oak
S80°E
11.760m to 20d nail
in north face
up 1.176m
scribed S13BT
(1997)

Knights
Lake

S4°37'19"W
44.166

New bearing trees were blazed, scribed & painted red. A tag stating the bearing & distance was affixed to the tree. A nail was placed in the base of the tree and the distance was measured from the monument to the nail.



395059

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

LaVerne Leuelling 11-16-97
Date

Registered Land Surveyor No. 18089
NORTHERN LIGHTS SURVEYING & MAPPING

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 3:28 P M. Date: Dec. 8, 1997

Recorder Claudine Taylor

By K.F. Deputy

DOCUMENT NO. 395059

Statement of Evidence

Meander Corner on the south shore of Knights Lake, common to Sections 13 and 14, Township 142 North, Range 28 West, of the Fifth Principal Meridian, Cass County, Minnesota.

1672; General Land Office (G.L.O.) survey notes; Deputy Surveyor E.W. Griffin set a wooden post for the meander corner and referenced it with the following:

8" Red Pine (0.203m)	6" Red Pine (0.152m)
N67°W	S15°W
13 Links (2.615m)	15 Links (3.017m)

Said records are on file with the Secretary of State, St. Paul, Minnesota; copies of these records are on file with the Cass County Surveyor's Office, Walker, Minnesota.

1939; United States Department of Agriculture—Forest Service (U.S.D.A.—F.S.) Form 874—9; Civilian Conservation Corps Junior Engineer Ray DeFant recovered an iron monument at the meander corner position in good condition, from which he noted the original G.L.O. witnesses at record bearing and distance. He noted that the iron pipe he found was set by the Cass County Surveyor, and established the following reference:

20" Norway Pine (0.508m)
N48°W
13.86 feet (4.225m)
metal location poster

November, 1988; Northern Lights Surveying and Mapping, Inc. crew of Smith and Berg searched the immediate area of the meander corner and tied in the following evidence to their traverse:

0.203m Red Pine stump, measured S70°E 1.0m from a Red Pine with old tag.

June, 1997; Joe Foster of Northern Lights Surveying and Mapping, Inc. returned to the meander corner and found an iron pipe lying on its side, approximately 4.5m from the red pine tied in previously. He set a galvanized steel pipe with a 0.083m diameter stamped brass cap up 0.250m at the record bearing and distance from the found red pine cited in Form 874—9 of record. The following references were established:

0.142m Oak	0.490m Norway Pine	0.091m Ash	Steel Signpost
S60°E	N46°W 4.440m to 20d nail	N11°W	East
11.780m to 20d nail	in face	11.800m to 20d nail	1.082m
in north face	up 0.280m	in east face	sign 54—9
up 1.178m	scribe overgrown	up 0.734m	
scribed S13BT		scribed XX	

The 1929 iron pipe was placed on the northwest side of the set monument.

Northern Lights Surveying and Mapping, Inc. Slater Township Field Book #3, p. 14.

Coordinates:

Cass County North

Northing = 84,340.059 meters
Easting = 174,585.257 meters

State Plane Coordinate System
Minnesota North Zone
NAD 83

Northing = 334,335.012 meters
Easting = 824,713.994 meters

Latitude = 47°06'28.06759" North
Longitude = 93°55'27.85180" West