






That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me  
this 26<sup>th</sup> day of Feb., 2013.

Notary Public



This instrument was drafted by:

Robert Kovanen  
Cass County Surveyor  
P.O. Box 579  
Walker, MN 56484

## AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Corner to Sec.'s 20-21-28-29 T. 144N R. 29W No.

State of Minnesota, }  
 County of Cass } ss.

Peter J. Meyer, being first duly sworn, deposes and says:  
 That I reside at Cass Lake, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 3628.  
 I further depose and say that on the 7th day of January, 1963, I found the section corner of sections 20-21-28-29 which was evidenced by the remains of a resurvey by the General Land Office in 1926.  
 Found a 2 inch diameter iron post with a brass cap stamped T144N R29W marking corner  

S20	S21
S29	S28

 1926  
 Yellow birch 24 inch S18°W 55 links or 36.3 feet. (now a 26 inch birch S18°W 36.3 feet with scribe visible.)  
 Maple 8 inch S20°E 70 links or 46.2 feet (now a 13 inch maple S20°E 46.2 feet with scribe visible.)  
 White pine N82°30'W 89 links or 58.74 feet (now a 18 inch W. pine N83°W 58.74 feet with scirbe overgrown.)  
 and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of no new monument set as the G.L.O. brass cap is in good condition.

from which reference or witness monuments are located in the manner following:

Maple 13 inch S20°E 46.2 feet marked S 28 BT  
 White Pine 23 inch S25°W 62.2 feet marked S 29 BT  
 White pine 18 inch N83°W 58.74 feet marked BT  
 Steel sign post 72 inches long, set 24 inches in the ground with signs 54-4 attached  
 N46°E 7.35 feet.

All reference bearings are true bearings.

*Peter J. Meyer*  
 (Surveyor's Signature)  
 In the Presence of:  
*Berulah Hendricks*  
*Jane Ann Nelson*  
 Subscribed and sworn to before me at  
 Walker, Minnesota  
 this 3rd day of July, 1963.  
*Berulah Hendricks*  
 Notary Public  
 Deputy Register of Deeds  
 Cass County, Minnesota

## OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 3rd day of July, A.D., 1963 at 9 o'clock A.M.

Leonard P. Peterson  
 Register of Deeds

By *Berulah Hendricks* Deputy



SECTION \_\_\_\_\_ TOWNSHIP \_\_\_\_\_ RANGE \_\_\_\_\_ P.M.

