



-2-


That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.



Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me
this 26th day of Feb., 2013.



Notary Public



This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Section
Corner to Sec.'s 6-7-1-12 T. 111N R. 27-28W No. 420State of Minnesota, }
County of Cass } ss.

William H. Okerman, being first duly sworn, deposes and says:

That I reside at Bemidji, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807.

I further depose and say that on the 28th day of June, 1966, I found the Section corner of Sections 6-7-1-12

which was evidenced by G.L.O. resurvey of 1937
 a set concrete monument 2 feet long by 6 inches in diameter with brass cap marked
 White Oak 14 inch N57°E 73 links or 48.18 feet - Now a rotted Oak stump at correct
 bearing and distance. T111N R28W R27W
 S 1 | S 6
 S12 | S 7
 1937
 White Oak 16 inch S73½°E 86 links or 56.76 feet - Now a 20 inch Oak at correct
 bearing and distance.
 Ash 8 inch S65-3/4°W 27 links or 17.82 feet - Now a 12 inch Ash at correct bearing
 and distance - blaze visible.
 Ash 9 inch N79-3/4°W 19 links or 12.54 feet - Now a rotted Ash stump at correct
 bearing and distance.
 and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker
 consisting of no new marker set, used G.L.O. brass cap.

from which reference or witness monuments are located in the manner following:

G.L.O. White Oak 20 inch S73½°E 56.76 feet - rescribed S7 BT.

G.L.O. Ash 12 inch S65-3/4°W 17.82 feet - rescribed S12 BT.

Oak 5 inch N42°E 11.5 feet - scribed S6 BT.

Ash 5 inch N68°W 46.1 feet - scribed S1 BT.

Set a steel sign post 72 inches long with signs 54-4 and 54-2 attached due South 4.5 feet.

All reference bearings are true bearings.

William H. Okerman
 (Surveyor's Signature)

In the Presence of:

*Beulah Hendricks**Claudia Kayler*

Subscribed and sworn to before me at

Walker, Minnesota

this 17th day of November, 1966

Beulah Hendricks

---Notary Public---

Register of Deeds, Cass County, Minn.

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 17th

day of November, A.D., 1966

at 9 o'clock A.M.

Beulah Hendricks
Register of Deeds

By Deputy

SECTION _____ TOWNSHIP _____ RANGE _____ P.M. _____

