





That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me  
this 26<sup>th</sup> day of Feb., 2013.

Notary Public



This instrument was drafted by:

Robert Kovanen  
Cass County Surveyor  
P.O. Box 579  
Walker, MN 56484

## AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Section 13 - 24  
Corner to Sec.'s 18 - 19

T. 144 N  
144 N

R. 27 W  
26 W

No. 417

State of Minnesota, }  
County of Cass } ss.

William H. Okerman, being first duly sworn, deposes and says:  
That I reside at Bemidji, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807.  
I further depose and say that on the 27th day of June, 1966, I found the Section corner of Section's 13 - 24 - 18 - 19 which was evidenced by G.L.O. resurvey of 1937 a set concrete monument 2 feet long by 6 inches in diameter with brass cap marked:  
Norway Pine 6 inch N39 $\frac{1}{2}$ ° E 61 lks or 40.26 feet - Now a 13 inch Pine at correct bearing and distance - blaze visible.  
Norway Pine 16 inch S59° E 50 lks or 33.00 feet - Now a stump at correct bearing and distance - scribe visible.  
Norway Pine 10 inch S73 $\frac{1}{4}$ ° W 75 lks or 49.50 feet - Now a Pine stump at correct bearing and distance - scribe visible.  
and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of No new marker set, used G.L.O. brass cap

T144N
R27W   R26W
S13   S18
S24   S19
1937

from which reference or witness monuments are located in the manner following:

G.L.O. Norway Pine 13 inch N39 $\frac{1}{2}$ ° E 40.26 feet - rescribed S18 BT.  
Red Pine 10 inch N37° W 20.25 feet - scribed S13 BT.  
Red Pine 12 inch S52° W 33.75 feet - scribed S24 BT.  
Red Pine 10 inch S37° E 36.9 feet - scribed S19 BT.

Set a steel sign post 72 inches long with signs 54-4 and 54-2 attached due East 5.6 feet.

All reference bearings are true bearings.

*William H. Okerman*  
(Surveyor's Signature)

In the Presence of:  
*Beverly Hendricks*  
*Claudine Taylor*  
Subscribed and sworn to before me at  
Walker, Minnesota  
this 17th day of November, 1966  
*Beverly Hendricks*  
--Notary Public  
Register of Deeds, Cass County, Minn.

## OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 17th day of November, A.D., 1966 at 9 o'clock A.M.

*Beverly Hendricks*  
Register of Deeds

By Deputy



SECTION \_\_\_\_\_ TOWNSHIP \_\_\_\_\_ RANGE \_\_\_\_\_ P.M. \_\_\_\_\_

