





That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

  
\_\_\_\_\_  
Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me  
this 27<sup>th</sup> day of Feb., 20 13.

  
\_\_\_\_\_  
Notary Public



This instrument was drafted by:

Robert Kovanen  
Cass County Surveyor  
P.O. Box 579  
Walker, MN 56484

## AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Center North 1/16  
Corner to Sec. 1 T. 144N R. 30W No. 582State of Minnesota, }  
County of Cass } ss.

William H. Okerman, being first duly sworn, deposes and says:

That I reside at Bemidji, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807.

I further depose and say that on the 10th day of July, 1969, I found the Center North 1/16 corner of Section 1

which was evidenced by remains of the G.L.O. resurvey of 1930 consisting of 1 inch diameter iron post, 3 feet long with brass cap marked: - evidence destroyed by pipeline construction.

Post not found - evidence destroyed by pipeline construction. C  
N. Pine 15 inch S55°E 48.18 feet - not found - evidence destroyed by pipeline construction. N 1/16 S1  
C

W. Pine 24 inch N81°30'W 52.14 feet - not found - evidence destroyed by pipeline construction. 1930

This corner relocated by proportionate measurement between the NW 1/16 and NE 1/16.

and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of a 2 inch diameter, 5 foot long galvanized steel pipe filled with concrete and capped with a 3 inch diameter brass tablet stamped:

T144N R30W

C  
N 1/16 S1  
C

1969

R.L.S. No. 6807

from which reference or witness monuments are located in the manner following:

W. Oak 10 inch N25°W 44.37 feet scribed CN 1/16 S1 BT

W. Oak 8 inch N26°E 45.47 feet scribed CN 1/16 S1 BT

W. Oak 11 inch N59°E 119.50 feet scribed CN 1/16 S1 BT

Steel sign post 72 inches long due east 3.00 feet with Forest Service sign 54-4 attached.

All reference bearings are true bearings.

William H. Okerman  
(Surveyor's Signature)

In the Presence of:

Joyce E. Myler  
Clifford B. Henn

Subscribed and sworn to before me at

Cass Lake, Minnesota

this 10th day of June 1970

Gordon E. Close  
Notary Public

GORDON E. CLOSE

Notary Public, Cass County, Minn.

My commission expires July 28, 1971

## OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 5th

day of February A.D., 1971

at 9 o'clock A.M.

Beulah Hendricks  
Register of Deeds

By Deputy



SECTION \_\_\_\_\_ TOWNSHIP \_\_\_\_\_ RANGE \_\_\_\_\_ P.M. \_\_\_\_\_

