

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Standard South Quarter Corner of Section 32
Township 145 N , Range 27 W , 5th P.M.
STATE OF MINNESOTA, COUNTY OF CASS



A000601090

**OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON**

3/20/2014 11:04:04 AM

AS DOC #: A000601090

PAGES: 2

REC FEES: 0.00

**KATHRYN M. NORBY
CASS COUNTY RECORDER**

BY SR Dep

On 12-10-2012, found a(n): 1" Diameter Iron Pipe With A 2" Brass Cap Stamped "General Land Office Survey" Up 0.3'

- left monument as found
- lowered monument
- removed monument (explain)
- raised monument

On _____, set a(n): _____

See "Statement of Evidence" for further details (on back)

(reserved for recording data)

NOTE: Wooded Area

14" Norway Pine With Nail & Disk In West Face Up 1', Set Bearing Tag



14" Poplar With Nail & Disk In North Face Up 1', Set Bearing Tag



N 40° W
39.20'

N 30° E
34.62'

1" Diameter Iron Pipe With A 2" Brass Cap Stamped "General Land Office Survey" Up 0.3'

S 48° W
25.57'

S 75° E
40.14'

10" Norway Pine With Nail & Disk In North Face Up 1', Set Bearing Tag



14" Poplar With Nail & Disk In South Face Up 1', Set Bearing Tag



32

SC



"SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)

Ties are measured to center of monument unless otherwise noted.

UNITS = Metric English

UTM COORDINATES, ZONE 15

Northing: 17197921.300

Easting: 1361064.412

NAD 83/1996 HARN Adjustment.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Ross Wamre
signature

6/25/13
date

Ross Wamre, Minnesota License No. 45334



STATEMENT OF EVIDENCE: Standard Corner common to Section 32 Township 145 North, Range 27 West of the 5th Principal Meridian.

1871; G.R. Stuntz, for the Government Land Office established this corner and witnessed by

Y. Pine 12" North 20° West, 36 links
Aspen 6" North 28° East, 80 links

1929; USFS 874 form on file at the USFS office in Cass Lake, MN, shows that Friesen, USFS, recovered a rotten tamarack post in place 30" above ground on a blazed line running East and West. And witnessed the corner by

FSLP on Jack Pine 7" North 74° West, 29 links
Birch 8" North 68° East, 44 links, cut face

1934; USFS 874 form on file at the USFS office in Cass Lake, MN, shows that Earl M. Handy, Chief of party, found this corner witnessed by:

FSLP on the NE Face of a Jack Pine 7" North, 29 Links (1929 Tie)

1937; GLO dependent resurvey of the Eleventh Standard Parallel North, along the South boundary of Township 145 North, through a portion of Range 26 West and through Range 27 West, 5th Principal Meridian. Hal D. Craig found the remains of an original bearing tree and set an iron post, 3' long, 1" diameter, 27" in the ground with a stamped brass cap, witnessed by:

Norway Stump North 20° West, 36 links
A local bearing tree Jack Pine 7" North 80° West, 12 links
White Pine 6" North 41 1/4° East, 72 links
Jack Pine 6" North 46° West, 64 links

1961; USFS 874 form on file at the USFS office in Cass Lake, MN, shows that a USFS surveyor recovered a brass capped pipe in good condition 4 in. above ground witnessed by:

Norway Pine 10" North 8° East, 30 links
FSLP on the S Face of a Jack Pine 6" North 10° East, 17 Links

2010; A Kadrmas, Lee & Jackson survey crew found a 2" Stamped Brass cap on a 1" Iron pipe 0.3' above the ground, witnesses found and established as shown on the face of this certificate.

2012; Ross Wamre, RLS #45334, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.

Contacts pertaining to this corner are as follows:

Cass County Recorder's Office
Cass County Surveyors Office
United States Forest Service
Bureau of Indians Affairs – Bemidji

Cass County Engineers Office
Northern Engineering and Consulting Inc.
MnDOT – District Office 2
Bureau of Land Management (BLM)