


Index No. V 15

CASS COUNTY LAND CORNER RECORD

T. 138 R. 32 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N 1/4 34 Corner common to sections 27, 34



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1870  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species	<u>N. PINE</u>	<u>N. PINE</u>	_____
Diameter	<u>14"</u>	<u>16"</u>	_____
Bearing	<u>S49W</u>	<u>N26W</u>	_____
Distance	<u>27LKS</u>	<u>53LKS</u>	_____

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1912 By JOHN CURD  
Location filed County SURVEY RECORD BOOK 'A' P 415-417  
Monument TWO STAKE SET BY USHER AND HIS BIT: 16"  
W. PINE STUB N58E 50.8' SET BY 8X8X36" CONCRETE  
POST

Evidence of Subsequent Corner Restoration

Year of search Nov 2003 By B. GUNNE #17253  
Cert. of Svy. shows mon. set

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_