


Index No. C 9

CASS COUNTY LAND CORNER RECORD

T. 140 R. 30 M. 5TH Coordinates: X _____ Y _____
E 1/4 5 Corner common to sections 4, 5



EXISTING SURVEYS

Original Government Survey

Year surveyed 1865
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species	<u>OAK</u>	<u>ELM</u>	_____
Diameter	<u>8"</u>	<u>9"</u>	_____
Bearing	<u>S39W</u>	<u>S55E</u>	_____
Distance	<u>27.4K</u>	<u>21.4K</u>	_____

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1965 By R.F. SCHNEIDER
Location filed COUNTY BOOK 'D' P. 448
Monument END LIP. (NEW TIES)

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

Bearing Trees, Reference Objects

Species	<u>N. PINE</u>	<u>OAK</u>	<u>P. OAK</u>
Diameter	<u>24"</u>	<u>20"</u>	<u>12"</u>
Bearing	<u>N62E</u>	<u>N57W</u>	<u>S50W</u>
Distance	<u>13.8'</u>	<u>24.1'</u>	<u>15.55'</u>

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
PLAT - WITHAM'S STONY LAKE SHORES
R.F. SCHNEIDER 1966

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____