


T. 141 R. 28 M. 5TH Coordinates: X _____ Y _____
E114 4 Corner common to sections 3, 4



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1874
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees
Species N. PINE N. PINE
Diameter 20" 30"
Bearing N40W N69E
Distance 65 LKS. 23 LKS

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1918 By GLO
Location filed SECRETARY OF STATE
Monument FIND OLD GOUT BITS. DECAYED STUMP N74W
65 LKS, 16" PINE STUMP N69E 23 LKS SET 1X36" I.P.
W/BRASS CAP 114
54/53
1921

Evidence of Subsequent Corner Restoration

Year of search 1999 By ~~EDD~~ James Kramer
FD- 1/2" I.P. down 1.0' A certificate
was filed as #410194, on MN/Dot 1997
Survey info.

Bearing Trees, Reference Objects

Species R. OAK
Diameter 6"
Bearing N11 1/2 W
Distance 256 LKS

Bearing Trees, Reference Objects

P. Pole Witness Post N. Pine Twin Burr Oak
18" 20"
S 15° W N 90° E S 50° E S 25° E
117.80'* 27.60' 59.21'* 75.50'*

* distance to copper nail and disk

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____