


Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Corner common to sections _____



= Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed _____
Original monument _____

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species _____
Diameter _____
Bearing _____
Distance _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration

Year of search _____ By _____
Location filed:
Monument:

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed:
Monument:

Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Page _____ of _____

Corner common to sections _____


Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration Found

Year surveyed _____ By _____
Location filed:
Monument:

Year of search _____ By _____
Location filed:
Monument:

T. 142 R. 26 M. 5TH Coordinates: X _____ Y _____
NE 17 Corner common to sections 8, 9, 16, 17



EXISTING SURVEYS

Original Government Survey

Year surveyed 1872
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

	Bearing Trees			
Species	<u>R. OAK</u>	<u>W. PINE</u>	<u>N. PINE</u>	<u>N. PINE</u>
Diameter	<u>6"</u>	<u>14"</u>	<u>30"</u>	<u>24"</u>
Bearing	<u>N71E</u>	<u>S64E</u>	<u>N77W</u>	<u>S18W</u>
Distance	<u>21 LKS</u>	<u>30 LKS</u>	<u>46 LKS</u>	<u>63 LKS</u>

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1916 By JAMES FLYNN
Location filed COUNTY BOOK C P. 165
Monument FOUND OLD GOV. B.T.S. 30" N. PINE STUMP
N77W 46 LKS, 24" N. PINE STUMP S18W 63 LKS,
ROOTS W. PINE S64E 30 LKS, ROOTS OAK N71E
21 LKS

Evidence of Subsequent Corner Restoration

Year of search 1920 By JAMES FLYNN
BOOK C P. 387 FND 1916 CORNER SET
2 1/2 X 30" IRON MONUMENT
COUNTY RESURVEY 1920 'E-2'
1963, BILL OKERMAN (USFS) CERTIFICATE # 334, FND 2" I.P. W/CAP
SET BY FLYNN IN 1916, AND HIS 1916 B.T.S. SET 6" DIA CONCRETE MANU.
W/ 3" BRONZE TABLET.

	Bearing Trees, Reference Objects	
Species	<u>W. PINE</u>	<u>W. PINE</u>
Diameter	<u>STUMP</u>	<u>STUMP</u>
Bearing	<u>S68W</u>	<u>N13E</u>
Distance	<u>80.9'</u>	<u>42.9'</u>

Bearing Trees, Reference Objects				
OAK	OAK	MAPLE	DAK	CEDAR Post
<u>7"</u>	<u>8"</u>	<u>7"</u>	<u>11"</u>	<u>4x4x60"</u>
<u>N63W</u>	<u>N32E</u>	<u>S68E</u>	<u>S48W</u>	<u>EAST</u>
<u>50.2'</u>	<u>79.0'</u>	<u>92.4'</u>	<u>131.2'</u>	<u>32'</u>

J-9

Subsequent Corner Restoration

Year surveyed Apr 2004 By CCSO
Location filed #2004.001
Monument Found brass cap in concrete,
up 3.2', 2" ODIP on SE side.

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - OKERMAN - 1963

<u>12" R. Oak</u>	<u>N33°E</u>	<u>78.85' (1983)</u>
<u>10" Maple</u>	<u>S70°E</u>	<u>91.88' (1983)</u>
<u>8" Maple</u>	<u>S54°W</u>	<u>88.87' duplex nail</u>

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____