


Index No. N 15

CASS COUNTY LAND CORNER RECORD

T. 142 R. 27 M. 5TH Coordinates: X _____ Y _____
N 14 22 Corner common to sections 15, 22



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument POST

Bearing Trees

Species	<u>ELM</u>	_____	_____
Diameter	<u>6"</u>	_____	_____
Bearing	<u>N 50 E</u>	_____	_____
Distance	<u>25 LKS</u>	_____	_____

Original Evidence Found

Year of search _____ By _____
Monument found _____

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1921 By _____
Location filed COUNTY BOOK "C" P 432
Monument FND ELM BIT. 6" N 50 E 25 LKS FND 6LO
IRON W/ BRASS CAP

Bearing Trees, Reference Objects

Species	<u>BALSAM</u>	<u>ASPEN</u>	_____
Diameter	<u>5"</u>	<u>12"</u>	_____
Bearing	<u>S 15 E</u>	<u>N 45 E</u>	_____
Distance	<u>27.2'</u>	<u>22.2'</u>	_____

Evidence of Subsequent Corner Restoration

Year of search 1919 By GLO
FND WOOD STAKE & ELM BIT. SET 1 X 36" I.P.W/ BRASS CAP
1/4 515
522
1919

Bearing Trees, Reference Objects

ELM	<u>BALSAM</u>	_____
<u>10"</u>	<u>6"</u>	_____
<u>N 87 1/2 W</u>	<u>S 17 E</u>	_____
<u>57 LKS</u>	<u>41 LKS</u>	_____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
PLAT - ROGERS BEACH
JOHN E. HOWARD 1957

Certificate - Gary Stevenson - 1983
Doc. # 267662
Found spike, Set County Cast Iron
Monument. Ties: 12" Elm N 10 E 61.50';
12" Aspen N 63 W 38.09'; 9" Maple S 53 W
72.15'; Power Pole South 63.17'.

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____