


C E R T I F I C A T E O F L O C A T I O N O F G O V E R N M E N T C O R N E R

For the Northwest One-sixteenth Corner of Section 9, Township 144 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On May 2, 1985, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe with a 3 inch diameter brass tablet up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES  
(not to scale)

compass decl: 5° E




N 8° W, 18.16 feet to a 16d nail in a 24.1 inch diameter Norway Pine, double blazed and scribed "NW1/16 S9" and "BT".

3.0 ft

8 foot metal post with a USFS 54-2 "PROPERTY BOUNDARY" sign attached.

3.0 ft



8 foot metal post with USFS 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.



S 37° W, 68.88 feet to a 16d nail in a 9.3 inch diameter Jack Pine, double blazed and scribed "NW1/16 S9" and "BT".

S 11° E, 19.99 feet to a 16d nail in a 7.5 inch diameter Jack Pine, double blazed and scribed "NW1/16 S9" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*  
Kenneth L. Whitehorn

Date 9-24-85 Registration No. 14677

<sup>285577</sup>  
OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of Nov, 1985, at 10:15 A.M. and assigned DOCUMENT NUMBER 285577.

*Clouline Kayler*  
County Recorder

*MJ*

**STATEMENT OF EVIDENCE:** The Northwest One-sixteenth Corner of Section 9, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original survey of this township by Benjamin C. Baldwin, Deputy Surveyor, in 1876.

No record was found of establishment or visitations through the intervening years for this corner position. A thorough search of the area was conducted but no evidence of this corner position was recovered. Based on this information we established this corner position at the intersection of the North and West One-sixteenth Lines of said Section 9. The basis for the determination of these subdivisional lines are: Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700, coordinates on the corners of the Public Land Survey System. These coordinates were provided to the USDA-Forest Service (USFS) by Advance Surveying and Engineering Company, Minneapolis, Minnesota, under contract to perpetuate and restore the Public Land Survey System corners in this township.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary.