

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner of Section 2, Township 141 N., Range 28 W., 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

On 7/14/87 found a 2" GLO brass cap monument
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES



Not to scale

24" N.Pine
 N 47°E 7.40' (old BT)

24" N.Pine
 N 70°E 15.65' (old BT)

10" Red Oak
 S 32°W 31.15'

Trees double blazed, scribed, painted red and 54-3 Bearing Tree tag attached. Measurement taken to nail in side of tree.

Statement of evidence relative to this corner location is on back of page. 301666

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Walter P. Carr 11-23-87
SIGNATURE DATE

Registration No. 11395

- Land Surveyor
- County Surveyor

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 9:05 A.M. on the 16 day of Dec. A.D., 19 87

County Recorder Claudia Kaylon

By MS, Deputy

DOCUMENT NO. 301666

Statement of Evidence: Northeast Corner Section 2,T.141 N.,R.28 W.,5th P.M.

- 1873 US General Land Office survey set a wood post for this corner and marked the following bearing tree: 12" N.Pine N 65°W 87 lks.
- 1917 County Survey Record Book "B", pages 601-603, show a survey by E.B.Horst. He found the original BT and set a post. He marked the following bearings: 10" N.Pine N 18-35 E 35.7', 8" Poplar N 25-40 W 50.4', 10" N.Pine S 49-55 W 69.9'
- 1919 US General Land Office dependent resurvey found a 2" galv. I.P. and original BT. Set a 2"x36" I.P. with marked brass cap alongside found I.P. The following new bearings were marked: 10" N.Pine N 48½°E 12 lks., 12" N.Pine S 9°E 114.1ks., 6" Bl.Oak S 70 3/4°W 130 lks., 12" N.Pine N 30°W 193 lks.
- 1972 US Forest Service personnel found the GLO brass cap monument in good condition and remains of 1919 survey: N.Pine NE is now a 16" N.Pine at bearing & distance-scribe burned off, N.Pine SE is now a 20" N.Pine at bearing & distance-scribe burned off, Pine NW is now a 21" N.Pine at bearing & distance-scribe burned but visible, Oak SW is now a burned stump at bearing & distance. The following new bearings were marked: 17" N.Pine N 73° 16.20', 19" N.Pine S 44°E 18.10', 20" N.Pine S 51°W 70.50', all scribed. 6' Steel sign post WEST 6.80'. Willaim Okerman filed CERTIFICATE OF LOCATION OF GOVERNMENT CORNER.
- 1987 Walt Curo, under contract with the US Forest Service, finds GLO monument in good condition, the 1919 NE BT and a 1972 BT also NE. He files this certificate to update the 1972 certificate.