

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner, Section 25, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

In May, 1997, Northern Lights Surveying and Mapping, Inc. set a galvanized steel pipe with a brass cap as a perpetuation of the "lost" position established by Schneider during a private survey conducted in 1966.

SKETCH OF REFERENCE TIES & EVIDENCE

T.142N., R.26W.

T.142N., R.25W.

0.460m Norway Pine
N29°W
28.496m to 20d nail
in sw face
up 0.310m
scribed S24BT
(1986)



0.391m Norway Pine
N33°E
11.162m to 20d nail
in nw face
up 0.300m
scribed S19BT
(1986)

0.302m White Oak
N72°E
4.322m to 20d nail
in south face
up 0.190m
scribed S19BT
(1986)

New bearing trees were blazed, scribed & painted red. A tag stating the bearing & distance was affixed to the tree. A nail was placed in the base of the tree and the distance was measured from the monument to the nail.

Steel Signpost
North 0.956m
sign 54-9
(1997)

Section 24



Section 19

Section 25

Section 30

Section Corner
Galvanized Steel
Pipe
Stamped
Brass Cap
(1997)

0.396m Norway Pine
N79°E
6.920m to 20d nail
in south face
up 0.250m
scribed S19BT
(1997)



NOT TO SCALE

Bearings are Grid
North Minnesota
Central Zone, measured
with a hand compass
adjusted to 3° East
declination.

400504

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Deane Leuelling
Deane Leuelling Date 5-20-1998

Registered Land Surveyor No. 16089
NORTHERN LIGHTS SURVEYING & MAPPING

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 2:05 P.M. Date: June 1st, 1998

Recorder Claudine Taylor

By K.F. [Signature] Deputy

DOCUMENT NO. 400504