

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

[Signature]

Date: 9/6/01 License No: 21367

OFFICE OF THE COUNTY RECORDER
County of CASS

I hereby certify that this document was filed in the Office of the County Recorder at 10:55 o'clock A.M. on the 10th day of Sept., 20 01 A.D.

County Recorder Kathryn M. Norby

By: John C. Maeder, Deputy
DOCUMENT NO. 440137

MC #32 Corner of Section 33, Township 142 N, Range 31 W, 5TH P.M.

On 5/10/01 found a 2" IRON PIPE WITH CAP UP 24"

left monument as found, lowered monument, removed monument (explain)

On 7/30/01 placed a THE CAP WAS STAMPED AS SHOWN

decl: 5° E (ASSUMED)

SKETCH OF REFERENCE TIES

Not to Scale


LAT. 47° 04' 58.7452"
LONG. 94° 36' 05.4494"



3" ASH



N 64° W
4.70



S 73° W
4.20



12" BIRCH
WITH LINE BLAZE

LONG LAKE

CORNER IN HIGH VISIBILITY AREA.
NO SCRIBING ON B.T.S OR PAINTING.

Statement of evidence for this corner position is on the back of this page

STATEMENT OF EVIDENCE

Index No. V – 12-13

Meander Corner No. 32, Section 33, Township 142 North,
Range 31 West, Cass County, Minnesota

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 142 North, Range 31 West. A wood post was set to mark the corner position with the following witnesses: A 3" Willow, North 67 degrees West, 9 links; a 4" Poplar, South 19 degrees West, 21 links.

1915 County Survey Record Book "C", p. 514, shows a survey by John Curo. He found the original corner post and set a 2 1/4" x 48" iron monument.

1915 County Resurvey plat by John Curo, Cass County Surveyor, resurvey of Section 28, set 2 1/4" x 48" capped iron monument from original corner post with a Pit 30" x 30" x 12" West 6 feet.

2001 May 10, a Landecker & Associates, Inc. survey crew found a 2 1/4" x 48" capped iron monument and accessories as marked by the U.S. Forest Service in 2000: A 12" Birch, S 73 degrees W 4.20 feet with a line blaze front and back and a 3" Ash, N 64 degrees W 4.70 feet. Found a USFS location tag on back of Birch dated 9/3/52. Accepts the corner as a perpetuation of the original corner. The cap was stamped as shown.