


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

South 1/16th Corner common to Section 1, Township 141 North, Range 30 West and Section 6, Township 141 North, Range 29 West, of the Fifth Principal Meridian, Cass County, Minnesota. The corner is accepted as originally set by the GLO resurvey and subdivision of 1917.

SKETCH OF REFERENCE TIES
T 141 N, R 29-30 W



NOT TO SCALE

9" Maple
N56°W
15.13' to 60d Spike In
West face up 0.8'
2003

8' Steel fence post
North 2.68'
54-2 and 54-9 signs

1" Maple
N54°E
50.64' to 60d Spike In
NW face up 1.5'
1981

Section 1

Section 6

S1/16 Sec. 1-6
Brass Capped
Iron Pipe

CL of Rogers Point Road

7" Twin Maple
S24°E
81.63' to 60d Spike In
East face up 0.85'
2003

Bearings are Grid
North, Minnesota
Central Zone, measured
with a hand compass
adjusted to 3° East
declination.

Abstract Document
#480059

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

LoVerne Leuelling
LoVerne Leuelling Date 2-11-04
Licensed Land Surveyor No. 16089
Northern Lights Surveying & Mapping, Inc.

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 9:20 A.M. Date: 2-12-2004
Recorder Kathryn M. Deuby
By tlv Deputy
DOCUMENT NO. 480059

Statement of Evidence

Page 2 of 2

South 1/16th Corner common to Section 1, Township 141 North, Range 30 West and Section 6, Township 141 North, Range 29 West, of the Fifth Principal Meridian, Cass County, Minnesota.

1917: Earl G. Harrington, US Surveyor, set a 1"x36" iron pipe with a brass cap from which he made the following BT's:

12" Oak	12" Oak
S37E	S39 1/2°W
56 lks (36.96')	242 lks (159.72')

Page 162, G.L.O. Resurvey notes of 1917. Said notes are on file with the Secretary of State in Saint Paul, MN and copies are at the Cass County Surveyor's Office in Walker, MN.

September 14, 1981: Walter E. Curo and Paul Johnson found standing monument in good condition on the West edge of Township Road. They found no trace of the original BT's. They made the following BT's:

7" Maple	5" Maple	8" Red Oak	8' Steel Sign Post
N56°58'E	S61°16'W	S27°34'E	North
50.97'	41.38'	58.31'	3.0'

Certificate of Location of Government Corner by Walter Curo filed in Cass County as Doc. No. 262647 dated 5/7/82.

September 15, 1999: R. Main, United States Forest Service, found the monument. Notes that it is 11' West of the center line of FR #3744. USFS Book 3, Page 48.

September, 2003: Northern Lights Surveying and Mapping, found the monument in good condition. Found one BT, now an 11" Maple, N54°E, 50.64'. Made the following new BT's:

9" Maple	7" Twin Maple	11" Maple	8' Steel Sign Post
N56°W	S24°E	N54°E	North
15.13' to 60d Spike in	81.63' to 60d Spike in	50.64' to 60d Spike in	2.68'
West face up 0.8'	East face up 0.85'	NW face up 1.5'	1981
2003	2003	1981	

The original copy of the notes are on page 73, Book 1 for contract No. 53-6392-3-2 for the USFS and are on file at the Supervisors Office of the Chippewa National Forest in Cass Lake, Minnesota. Copies are in the office of Northern Lights Surveying & Mapping in Grand Rapids, MN.

Coordinates by Static GPS:

Cass County North

Northing = 191,859.34'
Easting = 452,803.68'

State Plane Coordinate System
Minnesota Central Zone
NAD 83 (HARN 96)

Y = 1,077,819.34'
X = 2,585,782.18'

Geodetic Coordinates:

Latitude = 47° 03' 19.0592"N
Longitude = 94° 24' 21.5771"W