

STATEMENT OF EVIDENCE**North Quarter Corner Section 30, Township 136 North, Range 29 West, 5th P.M.**

The Department of Natural Resources, Division of Lands and Minerals, contacted the following offices for information regarding this corner:

MN Secretary of State
Cass County Recorder
Cass County Surveyor
Landecker and Associates, Inc.

1870 The US General Land Office field notes, on file in the Secretary of State's office, indicate a post set at the corner with the following bearing trees:

10" N. Pine	N 6° E	22 Links (14.52')
10" B. Pine	S 12° E	34 Links (22.44')

1916 Field notes from a survey by E. B. Horst, County Surveyor, in Survey Record Book B, pages 334-338, on file in the Cass County Surveyor's office state that he searched for evidence of the corner but found nothing. He measured the north line of Section 30 to be 5180.40 feet. Horst established the corner proportionally and set a 2" x 48" iron monument at the corner. A distance of 2518.00 feet is shown to the Northwest corner and a distance of 2662.40 feet is shown to the Northeast corner of Section 30. No other ties were given.

2007 A Landecker and Associates, Inc. survey crew found a 2" iron pipe at the corner during the course of a survey in Section 30, Township 136 N, Range 29 W.

2009 In March, a DNR survey crew found a 2" iron pipe, up 0.5 feet, 2.5 feet east of a fence corner of fence lines running north, east and west. The iron pipe was accepted as the monument set at the corner by Horst in 1916 and new ties were created.

The Northeast Corner of Section 30 bears N 89°37'28" E 2662.43'.

The Northwest Corner of Section 30 bears S 89°37'08" W 2515.66'.

For more information on our survey in this area, please contact the MN DNR, Division of Lands and Minerals, Survey Section, 1601 Minnesota Drive, Brainerd, MN 56401