

Statement of Evidence:**East Quarter Corner of Section 30, Township 135 North, Range 30 West**

Oct. T.B. Walker GLO Deputy Surveyor set a wood post for the original
1869 corner and referenced it as follows:

6" Ironwood S20°E 22 links (14.52 feet)
13" Birch S58°W 30 links (19.80 feet)

Oct. E.B. Horst, LS 376, Deputy County Surveyor, Survey Book C,
1917 Record No. 388 page 72, on file in the CCSO, states "Go North
between sections 29 & 30 and look for 1/4 corner which is
gone."

Feb. B. Hippen CCSO technician, records of the CCSO, searched area
2009 2640 feet north of the record position of the northeast corner of
section 31. No evidence of the corner was found.

March B. Hippen CCSO technician, records of the CCSO, located a
2009 brook noted in the GLO land calls and searched area 4.5 chains
(297.00 feet) north of the brook. This position is 150 feet, more
or less, south of the position previously searched. No evidence of
the corner was found.

Dec. Craig E. Johnson, LS, CFedS, another search of the area found
no evidence of the corner or it's accessories, the land calls in
the GLO notes were examined and found to be inconclusive,
Johnson set a 1/2 iron pipe capped No. 44530, 0.2 feet below
the surface. The corner was established by single proportion on
line and mid way between the NE and SE corners of Section 30.

A000568478
OFFICE OF COUNTY RECORDER
CASS COUNTY MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON
02/23/2011 07:53:06 AM
AS DOC #: A000568478
PAGES: 2 REC FEES: 0.00
KATHRYN M. NORBY
COUNTY RECORDER