



Index No. N.0-17.0

Statement of Evidence

Northeast corner Section 22, Township 139 North, Range 25 West, 5th Principal Meridian.

Nov.16, Johnson and Thornton, GLO Deputy Surveyors, in the notes of the subdivision of Township 139 North, 1863 Range 25 West, set a post for the original corner and referenced it as follows:

7" W. Birch	N 40° E	12 links (7.92 feet)	10" Aspen	N 50° W	30 links (19.80 feet)
6" Aspen	S 40° E	13 links (8.58 feet)	6" R. Oak	S 52° W	32 links (21.12 feet)

The above record and original plat are archived with the Minnesota Historical Society, St. Paul, Minnesota, copies are on file with Cass County Highway Department/Surveyor's Office.

Jul 25, J.W.Curo, LS 1428, Cass County Surveyor, Survey Record 160, Book A, page 345, on file in the Cass 1909 County Highway Department/Surveyor's Office, states "We found the S.W. Oak plainly marked but up rooted also the stump of the NE Birch from which we set the stake by flat measure, after which they stand as follows: Old Oak B.T. S 47° W 21.12 feet: Old Birch B.T. N 16° E 7.92 feet: Set new bearings as follows:
8" Green Norway N 41°19' E 14.35 feet 8" Dead Red Oak N 27°36' W 28.79 feet

May 2, A.W.Moulster, Deputy County Surveyor, Survey Record 161, Book A, page 346, and Curo Field Book 48, 1910 page 81, on file in the Cass County Highway Department/Surveyor's Office, states "setting on S.W. cor of 14-139-25 which was set by Curo I run east".

Apr. 9, J. Curo, LS 1428, Curo Field Book 74, page 8, on file in the Cass County Highway Department/Surveyor's 1911 Office, states "We find a 4 x 4 post formerly set by me for the true corner set from old Gov't B.T.s & a cut out transit line run East by Wm Moulster."

Aug 26, M.A.Kemp, Deputy County Surveyor, Survey Record 280, Book B, page 181, on file in the Cass County 1912 Highway Department/Surveyor's Office, states "Set on corner to sections 14, 15, 22, 23, Twp. 139 Rg. 25, previously established by Curo. I took the following bearings at 8° Variation:
N.E. corner of school-house bears S. 26°38' W, 160.20 feet to corner of foundation in section 22."

1937 Civilian Conservation Corps personnel, Washburn Lake notes, Book 1, page 60, on file in the Minnesota Department of Natural Resources Offices, indicates set approx cor 2 1/2" birch w/metal tag 5280' from east tied in with center of road.

Jul. 7, B.Hippen, CCSO technician, records of the Cass County Highway Department/Surveyor's Office, set a 7/8 2004 inch outside diameter iron pipe, stamped 16459, up 0.1 foot, 2 feet, more or less, west of the intersection of the centerline tangents of County State Aid Highway Number 58, at the 1912 bearing and distance from the NE corner of the remains of the old school foundation. The position agrees with the 1910 record distance to the northeast corner of Section 23. The following witnesses were added:
16" R. Oak N 37° W 39.98 feet Cedar Sign Post S 87° E 24.79 feet
14" R. Oak N 50° E 40.71 feet NE Foundation S 26°38' W 160.20 feet

Nov. Northwestern Surveying and Engineering, Inc. crew of Bomstad and Williams recovered and located the 2014 2004 monument and witnesses. The monument, recovered and established references for the position are shown on the face of this document.

Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument set by the Cass County Surveyor's Office in 2004 and recovered in 2014 by NWSE is the correct perpetuation of this corner.