



A000670584

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

3/25/2021 10:31:12 AM

AS DOC #: A000670584

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SF Dep TX#: 170194

Index No. R.0-21.0


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner of Section 26, Township 137, Range 30, 5TH P.M.

STATE OF MINNESOTA, County of CASS

At the location shown on the sketch:

- On _____ found _____
- left monument as found, lowered monument, removed monument (explain)
- On 11/07/2019 placed an 1/2 inch pipe capped RLS 45875



I hereby certify that this document was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota

Paul Herkenhoff
PAUL HERKENHOFF

N= 283796.968 E= 509346.835

DATUM= CASS COUNTY SOUTH

NAD 83/96 ADJ.

US SURVEY FT.

Date 2/11/2021 License No. 45875

Statement of evidence relative to this corner is on back of page.

Page 1 of 2

A000670584





13730R.0-21.0

Statement of Evidence

R-21, Northeast Corner of Section 26, Township 137 North, Range 30 West, 5th Principal Meridian.

1870 R.Cronk, General Land Office (GLO) Deputy Surveyor, in the notes of the subdivision of Township 137 North, Range 30 West, set a post for this original corner and referenced it as follows:

8" Tamarack N 85-1/2°E 250 links 9" White Birch S 58°E 360 links

Said records are on file with the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the Cass County Surveyor's Office (CCSO).

1908 John W. Curo, Cass County Surveyor noted finding a stake set by Canfield and the stump of the original birch accessory. Filed in Curo Book 85, Page 245, which is on file at the Cass County Surveyors office.

1910 John W. Curo, Cass County Surveyor noted recovering the previously mentioned 1908 stake. Filed in Curo Book 91, Page 24, which is on file at the Cass County Surveyors office.

1993 Bruce Grivna, RLS 17253 shows spike set at centerline-centerline of existing roads, filed in the Cass County Surveyors office.

Nov.
2019 Lakes Area Surveying searched for all previous evidence. This corner was set obliterated using road occupation East and South, agreeing with the 1993 survey. This position also agrees closely with the 1910 Curo survey, which is a direct perpetuation of the original GLO Survey. Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument set in November of 2019 by Lakes Area Surveying is the accepted location of this corner.