


T. 142 R. 26 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
m.c. # 10 Corner common to sections 13, 24



o = Corner

EXISTING SURVEYS

**Original Government Survey**

Year surveyed 1872  
Original monument POST

Species	Bearing	Trees
<u>N. PINE</u>	<u>N. PINE</u>	
<u>8"</u>	<u>24"</u>	
<u>N5E</u>	<u>N1E</u>	
<u>10LKS</u>	<u>14LKS</u>	

**Original Evidence Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

**Subsequent Corner Restoration**

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration**

Year of search 1997, July By Laverne Lewelling  
Monumented witness corner 25.000 meters easterly  
of meander corner position established on line between  
ne + nw corners of Sec. 24 at record distance from the  
gate NE corner of Sec. 24  
Cert. Filed: Dec. 8, 1997; Doc. # 395065

**Bearing Trees, Reference Objects**

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

**Bearing Trees, Reference Objects**

Species	Diameter	Bearing	Distance
<u>Ash</u>	<u>0.152m</u>	<u>N58W</u>	<u>9.430m</u>
<u>Red Pine</u>	<u>0.559m</u>	<u>N74W</u>	<u>4.704m</u>
<u>Birch</u>	<u>0.229m</u>	<u>S38W</u>	<u>3.998m</u>
<u>St Signpost</u>		<u>N</u>	<u>0.84m</u>

**Subsequent Corner Restoration**

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_